



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH EX TR T 250X30-80. FOR TABLE SAWS

SKU: 3165140881098

EX TR T 250x30-80. For table saws

Categories: [Accessories for BOSCH professional](#), [Saws](#)

Product Features: Outer diameter mm: 250

Bore size mm: 30

Bore with reduction ring mm: 0

Width of cut (b1) mm: 2,8

Base blade thickness (b2) mm: 1,8

Width of cut (b1) mm / Base bl. thickness (b2) mm: 2.8/1.8

Number of teeth: 80

Tooth shape: HLTCG

Max. rotation speed (RPM): 7600

Cutting result: 1

Pin hole/Pitch circle diameter: 2/7/42

Pin hole/Pitch circle diameter: 2/9.5/46.5

Pin hole/Pitch circle diameter: 2/9/46

Pin hole/Pitch circle diameter: 2/10/60

Hook angle °?: 10

Relief angle °?: 15

Benefit HL (short): Perfect Performance in High Pressure Laminate

Performance Claim Text: Perfect

Performance

(Version) Key RTB: Extra Hard MicroteQ teeth (Bosch in-house produced) from highly durable carbide grains for handling extreme conditions

Specific RTB1: Extra Hard MicroteQ teeth (Bosch in-house produced) from highly durable carbide grains for handling extreme conditions

Specific RTB2: Anti-vibration slots for particularly smooth cutting, considerably less noise and significantly reduced vibration

Specific RTB3: HLTCG (High-Low Triple Chip



Ground) teeth make the blade robust for working with abrasive materials

Material: HPL High-pressure laminate

Material: Solid surface composite

SOL Date: 01.10.2016

Novelty: no

Scope of delivery:

1 ST EX TR T 250x30-80. For table saws |

PRODUCT DESCRIPTION

The Expert for High Pressure Laminate Circular Saw Blade performs perfectly when cutting in high-pressure laminate. The blade's unique Extra Hard Microteq teeth are manufactured in-house by Bosch from highly durable carbide grains. The fine quality woodworkers expect, providing the capability to handle the extreme conditions of professional construction. This high-performance cutting is also strengthened by the blade's ProteQtion coating that prevents corrosion and delivers reliable cutting while reducing friction. Additionally, this product is specially designed with anti-vibration slots for particularly smooth cutting, considerably less noise and significantly reduced vibration. Use this saw blade in high-pressure laminate panels. Featuring HLTCG (High-Low Triple Chip Ground) teeth, the Expert for High Pressure Laminate Circular Saw Blade is robust for working with abrasive materials.

Article ID: 2608644359

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.