



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

ROBERT BOSCH POWER TOOLS GMBH FORSTNER DRILL BIT 22MM. FOR ROTARY DRILLS/DRIVERS

SKU: 3165140857970

Forstner drill bit 22mm. For rotary
drills/drivers

Categories: [Accessories for BOSCH professional](#), [Drilling](#)

Product Features: Diameter (D) mm: 22,00
Total length (L2) mm: 90
Shank diameter (d) mm: 8
Benefit HL (short): Excellent Lifetime for Drilling Accurate-Fit Holes
Performance Claim Text: Excellent Lifetime (Version) Key RTB: The tooth-edge design creates less friction and heat for increased durability
Specific RTB1: A short centring tip with two main and one periphery (toothed-edge) cutting edges enable smooth splinter-free drilling
Specific RTB2: Large chip-free zones for optimised chip removal and fast drilling accuracy
Specific RTB3: 3-sided shank prevents spinning in the chuck. Manufactured to DIN 7483G, 50 HRC (min) cutter hardness
Material: Softwood
Material: Hardwood
Material: Chipboard
Material: Pressure treated lumber
Material: Construction wood with mortar and nails
Material: Medium density fibreboard
Material: Multiplex board
Product text, Accessories grey: Pack of 1
SOL Date: 30.06.2016
Novelty: no



Scope of delivery:
1 ST Forstner drill bit 22mm. For rotary
drills/drivers |







PRODUCT DESCRIPTION

The Forstner Bit delivers excellent lifetime for drilling accurate-fit holes. Its toothed-edge design creates less friction and heat for increased durability. The precision drill bit's short centring tip has two main and one periphery (toothed-edge) cutting edges for spot-on results. Equipped with large chip-free zones, which allow for optimised chip removal, the bit's fast drilling accuracy is further supported. It enables the smooth splinter-free drilling of blind holes as well as edge and slant drilling, e.g. fixing hinges, dowelling and the removal of knotholes. Use when drilling in soft and hard wood, veneered wood and non-laminated chipboard. The Forstner Bit's 3-sided shank prevents spinning in the chuck. It is manufactured to DIN 7483G, cutter hardness is 50 HRC minimum.

Article ID: 2608577007

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.