



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

**ROBERT BOSCH POWER TOOLS GMBH  
HSS TWIST DRILL BIT POINTTEQ  
2.4MM. FOR ROTARY DRILLS/DRIVERS**

**SKU:** 3165140907019

HSS Twist Drill Bit PointTeQ 2.4mm. For  
rotary drills/drivers

---

**Categories:** [Accessories for BOSCH](#)  
[professional](#), [Drilling](#)

**Product Features:** Diameter (D) mm: 2,40  
Working length (L1) mm: 30  
Shank diameter (d) mm: 2,4  
Benefit HL (short): Fast Drilling in Metal  
Performance Claim Text: Fast Drilling in Metal  
(Version) Key RTB: Self-centering tip prevents  
wandering, making quick and easy drilling  
starts possible  
Specific RTB1: Increased drilling rate  
generates less heat and wear  
Specific RTB2: PointTeQ tip design remains  
sharp and ensures continuous durability  
Specific RTB3: Low risk of breakage due to  
highly elastic body, black-oxide coated flute;  
DIN 338, Type N, 135-degree tip  
Material: Steel  
Material: Cast iron  
Material: Metal pipes and profiles  
Material: Non-ferrous metals  
Material: Aluminium  
Material: Plastics  
Material: Metal sandwich  
Product text, Accessories grey: Pack of 10  
SOL Date: 01.09.2017  
Novelty: no  
Novelty until: 01.03.2018

Scope of delivery:  
1 ST HSS Twist Drill Bit PointTeQ 2.4mm. For  
rotary drills/drivers |









## PRODUCT DESCRIPTION

The HSS Twist Drill Bit PointTeQ enables fast drilling in metal due to its PointTeQ tip design. Quick and easy drilling starts are possible as the self-centering tip prevents wandering. Because of its increased drilling rate, less heat and wear are generated. The PointTeQ tip design remains sharp and ensures continuous durability. This bit is suitable for drilling clearance and pilot holes in alloyed and non-alloyed steel, non-ferrous metals, cast steel, cast iron and plastics. There is a low risk of breakage, especially for drill bits below 6 mm in diameter as the bit is manufactured to have a highly elastic body. Its black-oxide coated flute provides fast chip removal. The HSS Twist Drill Bit PointTeQ is manufactured to DIN 338. The drill bit is Type N (flute angle) with a tip of 135 degrees.

Article ID: 2608577192

### PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.