



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

ROBERT BOSCH POWER TOOLS GMBH IMPACT DRILL GSB 13 RE

SKU: 3165140371902

Impact Drill GSB 13 RE



Categories: [BOSCH professional](#), [Drills & percussion drills](#)

Product Features: Tool dimensions (height):

180 mm

Packaging dimensions (width): 261 mm

Packaging dimensions (length): 300 mm

Packaging dimensions (height): 75 mm

Packaging dimensions (width x length x height): 261 x 300 x 75 mm

Drill chuck, version: Keyless chuck

Voltage, electrical, up to: 230 V

Voltage, electrical: 230 V

Spindle collar diameter: 43,0 mm

Bit holder: 1/2"-20 UNF

Rated input power: 600 W

No-load speed, 1st gear, from: 0 rpm

No-load speed, 1st gear, up to: 2.800 rpm

No-load speed, 1st gear: 0 - 2,800 rpm

Power output: 301 W

Weight: 1,8 kg

Tool dimensions (width): 266 mm

Tool dimensions (length): 180 mm

Impact rate at no-load speed, 1st gear, from: 0 bpm

Impact rate at no-load speed, 1st gear, up to: 44.800 bpm

Impact rate at no-load speed: 0 - 44,800 bpm

Drilling dia. in wood, from: 25 mm

Drilling diameter in wood: 25 mm

Drilling dia. in steel, from: 10 mm

Drilling diameter in steel: 10 mm

Rated torque, 1st gear: 1,8 Nm

Rated torque: 1.8 Nm

Drill spindle connecting thread: 1/2"-20 UNF

Chuck capacity, min.: 1,5 mm



Chuck capacity, max.: 13 mm
Chuck capacity, min./max.: 1.5 - 13 mm
Drilling dia. in masonry, from: 15 mm
Drilling diameter in masonry: 15 mm
Vibration emission value ah [Drilling in metal]: 3,0 m/s²
Uncertainty K [Drilling in metal]: 1,5 m/s²
Vibration emission value ah [Impact drilling in concrete]: 26,0 m/s²
Uncertainty K [Impact drilling in concrete]: 3,0 m/s²
Vibration emission value ah [Screwdriving]: 2,5 m/s²
Uncertainty K [Screwdriving]: 1,5 m/s²
Product category subdivision: Impact Drill
Positioning: Compact 1-gear entry-level impact drill
User benefit incl. Reason to believe: 1.8 kg lightweight design and compact housing size provide for convenience in handling and manoeuvrability
User benefit incl. Reason to believe: Robust design with a durable metal keyless chuck
User benefit incl. Reason to believe: Delivers professional results at an optimum price performance value
Positioning (BE): Compact power - The most compact and powerful impact drill in its class
User benefit incl. Reason to believe (BE): Robust and powerful 600 W motor
User benefit incl. Reason to believe (BE): Extremely handy: No bigger than a glove and 1.7 kg light
User benefit incl. Reason to believe (BE): Soft in line grip for a secure hold
Areas of application: Drilling in concrete
Areas of application: Drilling in ferrous metals
Areas of application: Drilling in wood
Areas of application: Drilling in synthetic material
Areas of application: Drilling in non-ferrous metal
Areas of application: Drilling in stone
Areas of application: Dry drilling in stone
Areas of application: Screwdriving
Areas of application: Brushing coating material
Areas of application: Brushing ferrous metals



Areas of application: Brushing wood
Areas of application: Brushing non-ferrous metal
Title: Impact Drill GSB 13 RE Professional
Novelty: no
Scope of supply: Depth stop 210 mm (2 603 001 019)
Scope of supply: Keyless chuck 13 mm (2 608 572 149)
SOL Date: 01.09.2005

Scope of delivery:
1 ST Impact Drill GSB 13 RE |

PRODUCT DESCRIPTION

Impact Drill GSB 13 RE, The GSB 13 RE Professional is a compact corded 1-gearred entry-level impact drill. Its 1.8 kg lightweight design and small housing size provide convenience in handling and manoeuvrability. It is also particularly robust, including a durable metal keyless chuck. Additionally, this impact drill delivers professional results at an optimum price performance value. This tool is intended for drilling in masonry, stone, wood, and metal. The GSB 13 RE Professional also includes features such as speed selection and variable speed. Depth stop 210 mm (2 603 001 019); Keyless chuck 13 mm (2 608 572 149)

Article ID: 0601217100

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.