Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH IMPACT DRILL GSB 20-2

SKU: 3165140969178

Impact Drill GSB 20-2

Categories: BOSCH professional, Drills & percussion drills

Product Features: Torque, max., 2nd gear: 15,5 Nm
Packaging dimensions (width): 400 mm
Packaging dimensions (length): 439 mm
Packaging dimensions (height): 122 mm
Packaging dimensions (width x length x height): 400 x 439 x 122 mm
Drill chuck, version: 13-mm keyless chuck
Voltage, electrical, up to: 230 V
Voltage, electrical: 230 V
Bit holder: 1/2"-20 UNF
Rated input power: 850 W
No-load speed, 1st gear, from: 0 rpm
No-load speed, 1st gear, up to: 1.000 rpm
No-load speed, 1st gear: 0 - 1,000 rpm
No-load speed, 2nd gear, from: 3.000 rpm
No-load speed, 2nd gear: 3,000 rpm
Power output: 430 W
Weight: 2,6 kg
Tool dimensions (width): 90 mm
Tool dimensions (length): 336 mm
Tool dimensions (height): 214 mm
Impact rate at no-load speed, 1st gear, from: 0 bpm
Impact rate at no-load speed, 1st gear, up to: 17.000 bpm
Impact rate at no-load speed, 2nd gear: 51.000 bpm
Impact rate at no-load speed: 0 - 17,000 / 51,000 bpm
Drilling dia. in wood, from: 40 mm
Drilling dia. in wood, up to: 25 mm
Drilling diameter in wood: 40 / 25 mm

Copyright © 2023 Actik Tools All rights reserved

Drilling dia. in steel, from: 13 mm
Drilling dia. in steel, up to: 8 mm
Drilling diameter in steel: 13 / 8 mm
Rated speed, 1st gear: 800 rpm
Rated speed, 2nd gear: 2.060 rpm
Rated speed: 800 / 2,060 rpm
Rated torque, 1st gear: 5,2 Nm
Rated torque, 2nd gear: 2,0 Nm
Rated torque: 5.2 / 2.0 Nm
Drill spindle connecting thread: 1/2"-20 UNF
Chuck capacity, min.: 1,5 mm
Chuck capacity, max.: 13 mm
Chuck capacity, min./max.: 1.5 - 13 mm
Torque, max., 1st gear: 36,0 Nm
Max. torque: 36.0 Nm
Drilling dia. in stone, from: 20 mm
Drilling dia. in stone, up to: 15 mm
Drilling dia. in stone: 20 / 15 mm
Drilling dia. in masonry, from: 20 mm
Drilling dia. in masonry, up to: 15 mm
Drilling diameter in masonry: 20 / 15 mm
Vibration emission value ah [Drilling in metal]: 3,0 m/s²
Uncertainty K [Drilling in metal]: 1,5 m/s²
Vibration emission value ah [Impact drilling in concrete]: 15,0 m/s²
Uncertainty K [Impact drilling in concrete]: 2,0 m/s²
Vibration emission value ah [Screwdriving]: 2,5 m/s²
Uncertainty K [Screwdriving]: 1,5 m/s²
Vibration emission value ah [Thread-cutting]: 2,5 m/s²
Uncertainty K [Thread-cutting]: 1,5 m/s²
Product category subdivision: Impact Drill
Positioning: All-round performing 2-gear corded impact drill with KickBack Control
User benefit incl. Reason to believe: Powerful 850 W motor for fast work progress
User benefit incl. Reason to believe: KickBack Control increases user protection
User benefit incl. Reason to believe: Sturdy metal gear housing for a long tool lifetime
Positioning (BE): All-round performing 2-gear corded impact drill with KickBack Control
User benefit incl. Reason to believe (BE): Powerful 850 W motor for fast work progress
User benefit incl. Reason to believe (BE):

Copyright © 2023 Actik Tools All rights reserved

KickBack Control increases user protection
User benefit incl. Reason to believe (BE): Sturdy metal gear housing for a long tool lifetime
Areas of application: Drilling in concrete
Areas of application: Drilling in ferrous metals
Areas of application: Drilling in wood
Areas of application: Drilling in synthetic material
Areas of application: Drilling in non-ferrous metal
Areas of application: Drilling in stone
Title: Impact Drill GSB 20-2 Professional
Novelty: no
Novelty until: 01.07.2019
Scope of supply: Keyless chuck 13 mm (2 608 572 149)
Scope of supply: Auxiliary handle (2 605 025 190)
Scope of supply: Depth stop 210 mm (1 613 001 010)
Scope of supply: 7-piece masonry drill bit set CYL-1 (3/4/5/6/6/7/8 mm) (2 607 017 079)
Scope of supply: L-CASE
SOL Date: 01.01.2019

Scope of delivery:
1 ST Impact Drill GSB 20-2 |

PRODUCT DESCRIPTION

Impact Drill GSB 20-2, The GSB 20-2 Professional is the all-round performing 2-gear corded impact drill with KickBack Control. Its powerful 850 W motor enables fast work progress. User protection is increased by its intelligent KickBack Control feature. Additionally, the impact drill is designed with a sturdy metal gear housing that ensures a long tool lifetime. This tool is intended for drilling in masonry, stone, wood, and metal. It is compatible with the dust attachment GDE 16 Cyl Professional. The GSB 20-2 Professional also features Autolock, rotation control clutch, and speed selection. Keyless chuck 13 mm (2 608 572 149); Auxiliary handle (2 605 025 190); Depth stop 210 mm (1 613 001 010); 7-piece masonry drill bit set CYL-1 (3/4/5/6/6/7/8 mm) (2 607 017 079); L-CASE

Article ID: 060117B401

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information

Copyright © 2023 Actik Tools All rights reserved

about the product can be found on our website.

Copyright © 2023 Actik Tools

All rights reserved