



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



## ROBERT BOSCH POWER TOOLS GMBH IMPACT DRILL GSB 24-2

**SKU:** 3165140944519

Impact Drill GSB 24-2

**Categories:** [BOSCH professional](#), [Drills & percussion drills](#)

### **Product Features:** Torque, max., 2nd gear:

14,5 Nm

Packaging dimensions (width): 393 mm

Packaging dimensions (length): 441 mm

Packaging dimensions (height): 122 mm

Packaging dimensions (width x length x height): 393 x 441 x 122 mm

Drill chuck, version: 13-mm keyless chuck

Rated input power: 1.100 W

No-load speed, 1st gear, from: 0 rpm

No-load speed, 1st gear, up to: 900 rpm

No-load speed, 1st gear: 0 - 900 rpm

No-load speed, 2nd gear, from: 3.000 rpm

No-load speed, 2nd gear: 3,000 rpm

Power output: 630 W

Weight: 2,9 kg

Tool dimensions (width): 81 mm

Tool dimensions (length): 363 mm

Tool dimensions (height): 220 mm

Impact rate at no-load speed, 1st gear, from: 0 bpm

Impact rate at no-load speed, 1st gear, up to: 15.300 bpm

Impact rate at no-load speed, 2nd gear: 51.000 bpm

Impact rate at no-load speed: 0 - 15,300 / 51,000 bpm

Drilling dia. in wood, from: 40 mm

Drilling dia. in wood, up to: 25 mm

Drilling diameter in wood: 40 / 25 mm

Drilling dia. in steel, from: 16 mm

Drilling dia. in steel, up to: 8 mm

Drilling diameter in steel: 16 / 8 mm



Rated speed, 1st gear: 580 rpm  
Rated speed, 2nd gear: 1.900 rpm  
Rated speed: 580 / 1,900 rpm  
Rated torque, 1st gear: 9,6 Nm  
Rated torque, 2nd gear: 3,2 Nm  
Rated torque: 9.6 / 3.2 Nm  
Chuck capacity, min.: 1,5 mm  
Chuck capacity, max.: 13 mm  
Chuck capacity, min./max.: 1.5 - 13 mm  
Torque, max., 1st gear: 40,0 Nm  
Max. torque: 40.0 Nm  
Drilling dia. in stone, from: 24 mm  
Drilling dia. in stone, up to: 16 mm  
Drilling dia. in stone: 24 / 16 mm  
Drilling dia. in masonry, from: 24 mm  
Drilling dia. in masonry, up to: 16 mm  
Drilling diameter in masonry: 24 / 16 mm  
Vibration emission value ah [Drilling in metal]: 5,6 m/s<sup>2</sup>  
Uncertainty K [Drilling in metal]: 1,5 m/s<sup>2</sup>  
Vibration emission value ah [Impact drilling in concrete]: 14,6 m/s<sup>2</sup>  
Uncertainty K [Impact drilling in concrete]: 1,8 m/s<sup>2</sup>  
Vibration emission value ah [Screwdriving]: 2,5 m/s<sup>2</sup>  
Uncertainty K [Screwdriving]: 1,5 m/s<sup>2</sup>  
Vibration emission value ah [Thread-cutting]: 2,5 m/s<sup>2</sup>  
Uncertainty K [Thread-cutting]: 1,5 m/s<sup>2</sup>  
Product category subdivision: Impact Drill  
Positioning: 2-gear impact drill for toughest applications with KickBack Control  
User benefit incl. Reason to believe: Strong 1,100 W high-performance motor and high torque make it ideal for most heavy-duty applications  
User benefit incl. Reason to believe: KickBack Control increases user protection  
User benefit incl. Reason to believe: Sturdy metal gear housing for a long tool lifetime  
Positioning (BE): The powerful tool for toughest applications - now with the intelligent KickBack Control.  
User benefit incl. Reason to believe (BE): Heavy-duty applications with large diameters due to the 1,100 W Bosch high-performance motor and high torque



Areas of application: Drilling in concrete  
Areas of application: Drilling in ferrous metals  
Areas of application: Drilling in wood  
Areas of application: Drilling in synthetic material  
Areas of application: Drilling in non-ferrous metal  
Areas of application: Drilling in stone  
Areas of application: Dry drilling in stone  
Areas of application: Screwdriving  
Areas of application: Brushing coating material  
Areas of application: Brushing ferrous metals  
Areas of application: Brushing wood  
Areas of application: Brushing non-ferrous metal  
Title: Impact Drill GSB 24-2 Professional  
Novelty: no  
Novelty until: 01.12.2018  
Scope of supply: Keyless chuck 13 mm (2 608 572 150)  
Scope of supply: Auxiliary handle (2 602 025 193)  
Scope of supply: Depth stop 210 mm (1 613 001 010)  
Scope of supply: L-Case (1 600 A00 M7X)  
SOL Date: 01.06.2018

Scope of delivery:  
1 ST Impact Drill GSB 24-2 |

## PRODUCT DESCRIPTION

Impact Drill GSB 24-2, The GSB 24-2 Professional is a 2-gear corded impact drill with KickBack Control designed for the toughest jobs. Its strong 1,100 W high-performance motor and high torque make it ideal for most heavy duty applications. It also features KickBack Control for increased user protection. Equipped with a sturdy metal gear housing, this impact drill is extremely robust for a long tool lifetime. This tool is intended for drilling in masonry, stone, wood, and metal. It is compatible with the dust attachment GDE 16 Cyl Professional. The GSB 24-2 Professional includes features such as Autolock, rotation control clutch, and speed selection. Keyless chuck 13 mm (2 608 572 150); Auxiliary handle (2 602 025 193); Depth stop 210 mm (1 613 001 010); L-Case (1 600 A00 M7X)

Article ID: 060119C801

## PRODUCT DATASHEET LEGAL NOTE



Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.