



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH LASER RECEIVER LR 60

SKU: 3165140976473

Laser Receiver LR 60

Categories: [BOSCH professional](#), [Measuring equipment](#)

Product Features: Range, from: 0 m
Range, up to: 300 m
Range of: 0 - 300 m
Range, receiver, sign: <
Range, receiver, value: 300 m
Range: < 300 m
Power supply: 2 x 1.5 V LR6 (AA)
Dust and splash protection: IP 67
Weight, approx.: 380 g
Tool dimensions (width): 79 mm
Tool dimensions (length): 175 mm
Tool dimensions (height): 33 mm
Measuring accuracy, fine: ±0.5 mm, ±1mm, ±2mm, ±5mm, ±10mm
Measuring accuracy (fine/rough): ±0.5 mm, ±1mm, ±2mm, ±5mm, ±10mm
Suitable for: GRL 600 CHV
Type of receiver: Rotation lasers
Remote control: no
Receiver: no
Product category subdivision: Laser Receiver
Positioning: Laser detection made quick and easy - enjoy high-quality results with LR 60 Professional
User benefit incl. Reason to believe: Long 125-mm reception window and dual-sided backlit display for quick and easy laser detection
User benefit incl. Reason to believe: Heavy-duty design via robust, soft grip body, durable rubber keypad, and P67 protection rating against dust and water
User benefit incl. Reason to believe:



Communication with GRL 600 CHV
Professional for user calibration, dual Centre line mode, and GRL battery status
Title: Laser Receiver LR 60 Professional
Novelty: no
Novelty until: 01.08.2020
Scope of supply: Receiver bracket RB 60 Professional
Scope of supply: 2 x 1.5 V LR6 battery (AA)
SOL Date: 01.05.2020

Scope of delivery:
1 ST Laser Receiver LR 60 |

PRODUCT DESCRIPTION

Laser Receiver LR 60, Fast and easy laser detection - the robust, high-quality rotation laser receiver LR 60 Professional is the perfect mate when working with the GRL 600 CHV Professional. Its long 125-mm reception window and dual-sided backlit LCD display with a mm offset feature make it simple to detect lasers quickly and easily for efficient working progress. It is always ready for even the toughest jobsites thanks to its robust soft grip body, durable rubber keypad, and IP67 protection rating against dust and water. Communication with GRL 600 CHV enables additional functions including user calibration (uCAL) and Centre line mode for less errors and more reliable results. Use this receiver with the GRL 600 CHV when determining cut-and-fill for excavation work, concrete forms, landscaping, and facade work. The laser receiver LR 60 also features different sensitivity and volume settings, making it adaptable to fit each work environment. It has a large working range of up to 300 m. The receiver's LEDs with adjustable brightness settings help detect the laser beam while its vial ensures accurate results. Receiver bracket RB 60 Professional; 2 x 1.5 V LR6 battery (AA)

Article ID: 0601069P00

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.