Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH LINE LASER GLL 2-10

SKU: 3165140850247

Line Laser GLL 2-10

Categories: BOSCH professional, Measuring equipment

Product Features: Laser diode: 630 - 650 nm, < 1mW
Operating temperature, from: -10 °C
Operating temperature, up to: 50 °C
Operating temperature: -10 - 50 °C
Storage temperature, from: -20 °C
Storage temperature, up to: 70 °C
Storage temperature: -20 - 70 °C
Laser class: 2
Working range, value: 10 m
Working range: 10 m
Accuracy: ± 0.3 mm/m* (*plus use-dependent deviation)
Working range of laser crosses: 10 m
Self-levelling range: ± 4°
Levelling time: 4 s
Dust and splash protection: IP 54
Power supply: 3 x 1.5 V LR6 (AA)
Operating time (max.): 9 h in cross line mode
Operating time (max.): 17 h in line mode
Tripod thread: 1/4", 5/8"
Weight, approx.: 0,49 kg
Colour of laser line: red
Projection: 2 lines
Product category subdivision: Line Laser
Positioning: Compact and intuitive line laser for short-distance applications
User benefit incl. Reason to believe: Horizontal and vertical laser lines ideal for short-range applications
User benefit incl. Reason to believe: Compact design and intuitive operation for easy handling

Copyright © 2023 Actik Tools All rights reserved

User benefit incl. Reason to believe: Robust laser level partly due to IP54 dust and splash water protection
Title: Line Laser GLL 2-10 Professional
Novelty: no
Scope of supply: Protective Bag
Scope of supply: 3 x 1.5 V LR6 battery (AA)
SOL Date: 01.01.2017

Scope of delivery:
1 ST Line Laser GLL 2-10 |

PRODUCT DESCRIPTION

Line Laser GLL 2-10, The compact GLL 2-10 Professional makes interior levelling applications simple. With one horizontal and one vertical laser line, it is ideal for short-range work. Thanks to only one switch and two clear buttons, this compact line laser offers intuitive operation and great handling when doing levelling work. The GLL 2-10 Professional is robust with IP54 dust and splash water protection. It is suitable for various interior applications such as suspending drop-ceilings, mounting shelves, doors, and sockets; installing drainage pipes, and laying floor tiles. The GLL 2-10 Professional has a working range of up to 10 m and can self-level up to +/- 4° in less than 4 seconds. When the tool is switched off, the pendulum is locked for safe transport. Ideal for use with the optional rotating mount RM 1 Professional that can be swiftly attached via a simple slide mechanism. Protective Bag; 3 x 1.5 V LR6 battery (AA)

Article ID: 0601063L00

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.

Copyright © 2023 Actik Tools All rights reserved