Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

ROBERT BOSCH POWER TOOLS GMBH METAL DRILL BITS HSS-CO, DIN 338. FOR ROTARY DRILLS/DRIVERS

SKU: 3165140520881

Metal drill bits HSS-Co, DIN 338. For rotary drills/drivers

Categories: Accessories for BOSCH professional, Drilling

Product Features: Diameter (D) mm: 5,20
Working length (L1) mm: 52
Total length (L2) mm: 86
Benefit HL (short): Long Lifetime when Drilling Stainless Steel
Performance Claim Text: Long Lifetime
(Version) Key RTB: Cobalt alloy and fully ground HSS provide wear resistance and heat protection
Specific RTB1: Two cutters and two flutes remove chips quickly to make the bits last even longer
Specific RTB2: Manufactured to DIN 338, drill bit Type N (flute angle) with a 135-degree tip, diameter tolerance h8
Specific RTB3: Active cutting and perfect centring without wandering are achieved by the pointed split-point tip
Material: Stainless steel
Material: Metal pipes and profiles
Material: Steel sheets
Material: Plastics
Material: Metal sandwich
Product text, Accessories grey: Pack of 1
SOL Date: 26.03.2008
Novelty: no

Scope of delivery:
1 ST Metal drill bits HSS-Co, DIN 338. For rotary drills/drivers |

Copyright © 2023 Actik Tools All rights reserved

Copyright © 2023 Actik Tools

All rights reserved

Copyright © 2023 Actik Tools

All rights reserved



Copyright © 2023 Actik Tools

All rights reserved

PRODUCT DESCRIPTION

The HSS Twist Drill Bit Cobalt provides long-lasting performance when drilling stainless steel. This extended lifetime results from a cobalt alloy content of 5% and fully ground HSS (high-speed steel), which provides excellent surface quality, wear resistance and heat protection. Equipped with two cutters and two flutes, chips are removed quickly to make the bit last even longer. This drill bit works with alloyed and non-alloyed steel, stainless steel, cast iron, cast steel and acid- and heat-resistant steels. The HSS Twist Drill Bit Cobalt is manufactured to DIN 338. The drill bit is Type N (flute angle) with a 135-degree tip and a diameter tolerance of h8. Active cutting and perfect centring without wandering are achieved by the pointed split-point tip.

Article ID: 2608585853

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.

Copyright © 2023 Actik Tools All rights reserved