



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

## ROBERT BOSCH POWER TOOLS GMBH METAL DRILL BITS HSS-G, DIN 338. FOR ROTARY DRILLS/DRIVERS

**SKU:** 3165140521727

Metal drill bits HSS-G, DIN 338. For rotary drills/drivers

---

**Categories:** [Accessories for BOSCH professional](#), [Drilling](#)

**Product Features:** Diameter (D) mm: 10,50  
Working length (L1) mm: 87  
Total length (L2) mm: 133  
Benefit HL (short): Drilling with High Precision  
Performance Claim Text: Maximum Precision (Version)  
Key RTB: 135-degree self-centring split-point tip combines active cutting and perfect centring without wandering  
Specific RTB1: Precision-ground bit made of HSS enables fast results  
Specific RTB2: No need to pre-punch or pilot drill up to 10 mm-diameter  
Specific RTB3: Manufactured to DIN 338, drill bit Type N (flute angle) with a 135-degree tip, diameter tolerance h8  
Material: Steel  
Material: Cast iron  
Material: Metal pipes and profiles  
Material: Non-ferrous metals  
Material: Aluminium  
Material: Plastics  
Material: Metal sandwich  
Material: Steel sheets  
Product text, Accessories grey: Pack of 1  
SOL Date: 07.07.2008  
Novelty: no

Scope of delivery:  
5 ST Metal drill bits HSS-G, DIN 338. For rotary drills/drivers |









## PRODUCT DESCRIPTION

The HSS Twist Drill Bit Ground is for drilling through metal with maximum precision. The bit's exposed 135-degree self-centring split-point tip combines active cutting and perfect centring without wandering, delivering maximum precision. The split-point tip also eliminates any need to pre-punch or pilot drill for up to 10 mm. This precision-ground bit made of HSS (high-speed steel) enables up to 40% faster drilling rate and up to 50% lower feed pressure than standard-ground HSS drill bits with chisel edges. This bit is designed for drilling holes in alloyed and non-alloyed steel, cast steel, cast iron, sintered iron, malleable cast iron, non-ferrous metals and hard plastics. The HSS Twist Drill Bit Ground is manufactured to DIN 338. The drill bit is Type N (flute angle) with a 135-degree tip and a diameter tolerance of h8.

Article ID: 2608585937

### PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.