



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

**ROBERT BOSCH POWER TOOLS GMBH
METAL DRILL BITS HSS-G, DIN 338.
FOR ROTARY DRILLS/DRIVERS**

SKU: 3165140475334

Metal drill bits HSS-G, DIN 338. For rotary drills/drivers

Categories: [Accessories for BOSCH professional](#), [Drilling](#)

Product Features: Material: Metal pipes and profiles

Material: Non-ferrous metals

Material: Aluminium

Material: Plastics

Material: Metal sandwich

Material: Steel sheets

Product text, Accessories grey: Pack of 5

SOL Date: 07.07.2008

Novelty: no

Diameter (D) mm: 10,80

Working length (L1) mm: 94

Total length (L2) mm: 142

Benefit HL (short): Drilling with High Precision

Performance Claim Text: Maximum Precision

(Version) Key RTB: 135-degree self-centring

split-point tip combines active cutting and

perfect centring without wandering

Specific RTB1: Precision-ground bit made of

HSS enables fast results

Specific RTB2: No need to pre-punch or pilot

drill up to 10 mm-diameter

Specific RTB3: Manufactured to DIN 338, drill

bit Type N (flute angle) with a 135-degree tip,

diameter tolerance h8

Material: Steel

Material: Cast iron

Scope of delivery:

1 ST Metal drill bits HSS-G, DIN 338. For



rotary drills/drivers |







PRODUCT DESCRIPTION

The HSS Twist Drill Bit Ground is for drilling through metal with maximum precision. The bit's exposed 135-degree self-centring split-point tip combines active cutting and perfect centring without wandering, delivering maximum precision. The split-point tip also eliminates any need to pre-punch or pilot drill for up to 10 mm. This precision-ground bit made of HSS (high-speed steel) enables up to 40% faster drilling rate and up to 50% lower feed pressure than standard-ground HSS drill bits with chisel edges. This bit is designed for drilling holes in alloyed and non-alloyed steel, cast steel, cast iron, sintered iron, malleable cast iron, non-ferrous metals and hard plastics. The HSS Twist Drill Bit Ground is manufactured to DIN 338. The drill bit is Type N (flute angle) with a 135-degree tip and a diameter tolerance of h8.

Article ID: 2608585528

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.