



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

ROBERT BOSCH POWER TOOLS GMBH RECIPROCATING SAW BLADE S 1022 HF. FOR RECIPROCATING SAWS

SKU: 3165140293426



Reciprocating saw blade S 1022 HF. For reciprocating saws

Categories: [Accessories for BOSCH professional](#), [Saws](#)

Product Features: Wood with nails/metal

[mm]: <150

Pallets [mm]: <150

Sheet metal, pipes, profiles, from [mm]: 3

Sheet metal, pipes, profiles, to [mm]: 12

Sheet metals, pipes, profiles [mm]: 3-12

Tooth design: side set, milled

Tooth spacing [mm]: 2.5

Tooth pitch [TPI]: 10

Total length [mm]: 200

Total length [Inch]: 8

Width [mm]: 19

Thickness [mm]: 0,9

Blade material: BI-METAL

Blade material abbreviation: BIM

Body material: HCS

Max. cut capacity [mm]: 150

Areas of application: Wood with nails/metal (<150 mm), sheet metals, pipes, aluminium profiles (3-12 mm), pallets

Progressive: no

Type: S 1022 HF

Benefit HL (short): Flush Cuts for Pallet Repair

Performance Claim Text: Flush Cuts

(Version) Key RTB: Standard gauge material (0.9 mm) with standard length (200 mm) is ideal for flush cutting

Specific RTB1: BIM blade is optimised for pallet repair applications

Specific RTB2: Featuring a medium tooth pitch (2.5 mm), the blade cuts soft nails and



fasteners common in pallet construction
Specific RTB3: Standard length of 200 mm for a cutting capacity of up to 150 mm
Material: Wood with nails
Material: Plastics
Product text, Accessories grey: **S 1022 HF**
Product text, Accessories grey: BIM, side set, milled
Product text, Accessories grey: For pallet repair, wood with nails/metal (<150 mm), sheet metals, pipes, aluminium profiles (3-12 mm), flexible flush cut
SOL Date: 24.11.2004
Novelty: no

Scope of delivery:
1 ST Reciprocating saw blade S 1022 HF. For reciprocating saws |

PRODUCT DESCRIPTION

The S 1022 HF Flexible for Wood and Metal Reciprocating Saw Blade delivers flush cuts in wood and metal. Its standard gauge material (0.9 mm) with a standard length (200 mm) is ideal for flush cutting. Moreover, its BIM (bi-metal) base combines an HCS (high carbon steel) blade and an HSS (high-speed steel) tooth strip, making this reciprocating saw blade optimal for pallet repair applications. Featuring a medium tooth pitch (2.5 mm), the blade cuts soft nails and fasteners common in pallet construction. It is equipped with a standard length of 200 mm, providing a cutting capacity of up to 150 mm.

Article ID: 2608656636

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.