Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH RECIPROCATING SAW BLADE S 1122 EF. FOR RECIPROCATING SAWS

SKU: 3165140093446

Reciprocating saw blade S 1122 EF. For reciprocating saws

Categories: Accessories for BOSCH professional, Saws

Product Features: Sheet metals, thin, from [mm]: 1,5
Sheet metals, thin, to [mm]: 4
Sheet metals, thin [mm]: 1.5-4
Profiles, pipes: closed [mm]: <175
Profiles, pipes: open [mm]: <175
Tooth design: side set, milled
Tooth spacing [mm]: 1.4
Tooth pitch [TPI]: 18
Total length [mm]: 225
Total length [Inch]: 9
Width [mm]: 19
Thickness [mm]: 0,9
Blade material: BI-METAL
Blade material abbreviation: BIM
Body material: HCS
Recommended min. material thickness [mm]: 1,5
Recommended max. material thickness [mm]: 4
Max. cut capacity [mm]: 175
Areas of application: thin sheet metals (1.5-4 mm), pipes/profiles (diameter <175 mm), flexible flush cut
Progressive: no
Type: S 1122 EF
Benefit HL (short): Optimised for Flush Cutting in Metal Pipes
Performance Claim Text: Optimised for Flush Cutting
(Version) Key RTB: 225 mm length and

Copyright © 2023 Actik Tools All rights reserved

standard-gauge material thickness of 0.9 mm enable excellent flush cuts
Specific RTB1: Cuts steel materials with most common wall thicknesses thanks to blades fine tooth pitch (1.4 mm)
Specific RTB2: BIM blade is suitable for cutting regular-strength steel materials. Standard length of 225 mm has a 175 mm cutting capacity
Specific RTB3: Fine tooth pitch is ideal for use on pipes and profiles with a wall thickness of 1.5 mm to 4 mm
Material: Steel
Material: Non-ferrous metals
Product text, Accessories grey: **S 1122 EF**
Product text, Accessories grey: BIM, side set, milled
Product text, Accessories grey: Thin sheet metals (1.5-4 mm), pipes/profiles (diameter <175 mm), flexible flush cut
SOL Date: 19.07.2002
Novelty: no

Scope of delivery:
5 ST Reciprocating saw blade S 1122 EF. For reciprocating saws |

PRODUCT DESCRIPTION

The S 1122 EF Flexible for Metal Reciprocating Saw Blade is optimised for flush cutting in metal. Its 225 mm length and standard-gauge material thickness of 0.9 mm enable excellent flush cuts. Moreover, cutting steel materials with most common wall thicknesses is possible thanks to the blades fine tooth pitch (1.4 mm). Made of BIM (bi-metal), the blade is suitable for cutting regular-strength steel materials, while its fine tooth pitch is ideal for use on pipes and profiles with a wall thickness of 1.5 mm to 4 mm. The blades standard length of 225 mm provides a cutting capacity of up to 175 mm.

Article ID: 2608656042

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.

Copyright © 2023 Actik Tools All rights reserved