



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

ROBERT BOSCH POWER TOOLS GMBH RECIPROCATING SAW BLADE S 1122 HF. FOR RECIPROCATING SAWS

SKU: 3165140515283



Reciprocating saw blade S 1122 HF. For reciprocating saws

Categories: [Accessories for BOSCH professional](#), [Saws](#)

Product Features: Wood with nails/metal
[mm]: <175

Pallets [mm]: <175

Sheet metal, pipes, profiles, from [mm]: 3

Sheet metal, pipes, profiles, to [mm]: 12

Sheet metals, pipes, profiles [mm]: 3-12

Tooth design: side set, milled

Tooth spacing [mm]: 2.5

Tooth pitch [TPI]: 10

Total length [mm]: 225

Total length [Inch]: 9

Width [mm]: 19

Thickness [mm]: 0,9

Blade material: BI-METAL

Blade material abbreviation: BIM

Body material: HCS

Max. cut capacity [mm]: 175

Areas of application: for pallet repair, wood with nails/metal (<175 mm), sheet metals, pipes, aluminium profiles (3-12 mm), flexible flush cut

Progressive: no

Type: S 1122 HF

Benefit HL (short): Flush Cuts for Pallet Repair

Performance Claim Text: Flush Cuts

(Version) Key RTB: Standard gauge material (0.9 mm) with standard length (225 mm)

makes flush cutting possible

Specific RTB1: BIM blade is optimised for pallet repair applications

Specific RTB2: Featuring a medium tooth



pitch (2.5 mm), the blade cuts all soft nails and fasteners common in pallet construction
Specific RTB3: Standard length of 225 mm for a cutting capacity of up to 175 mm
Material: Wood with nails
Material: Plastics
Product text, Accessories grey: **S 1122 HF**
Product text, Accessories grey: BIM, side set, milled
Product text, Accessories grey: For pallet repair, wood with nails/metal (<175 mm), sheet metals, pipes, aluminium profiles (3-12 mm), flexible flush cut
SOL Date: 08.04.2008
Novelty: no

Scope of delivery:
1 ST Reciprocating saw blade S 1122 HF. For reciprocating saws |

PRODUCT DESCRIPTION

The S 1122 HF Flexible for Wood and Metal Reciprocating Saw Blade delivers flush cuts in wood and metal. Its standard gauge material (0.9 mm) with a standard length (225 mm) makes the blade capable of flush cutting. Moreover, its BIM (bi-metal) base combines an HCS (high carbon steel) blade with an HSS (high-speed steel) tooth strip, making this reciprocating saw blade optimal for pallet repair applications. Featuring a medium tooth pitch (2.5 mm), the blade cuts all soft nails and fasteners common in pallet construction. It is equipped with a standard length of 225 mm, providing a cutting capacity of up to 175 mm.

Article ID: 2608657560

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.