



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



## ROBERT BOSCH POWER TOOLS GMBH RECIPROCATING SAW BLADE S 1122 VFR. FOR RECIPROCATING SAWS

**SKU:** 3165140749312

Reciprocating saw blade S 1122 VFR. For reciprocating saws

---

**Categories:** [Accessories for BOSCH professional](#), [Saws](#)

**Product Features:** Pallets [mm]: 5-165

Tooth design: Vario toothing

Tooth spacing [mm]: 1.8-2.6

Tooth pitch [TPI]: 10-14

Total length [mm]: 225

Total length [Inch]: 9

Width [mm]: 19

Thickness [mm]: 0,9

Blade material: BI-METAL

Blade material abbreviation: BIM

Body material: HCS

Max. cut capacity [mm]: 165

Areas of application: Pallets, cutting depth up to 165 mm, maximum flexibility

Progressive: no

Type: S 1122 VFR

Benefit HL (short): Breakproof Blade for Smooth Flush Cuts

Performance Claim Text: Effortless Flush Cuts (Version) Key RTB: Reverse tip prevents jamming, bending and shank breakage for long life

Specific RTB1: Vario-tooth design for vibration-reduced, smooth cuts. BIM blade ideal for pallet repair applications

Specific RTB2: Standard gauge material (0.9 mm) and length provide excellent flush cuts

Specific RTB3: Fine to medium vario-tooth pitch cuts through soft nails and fasteners.

Standard length for a 165 mm cutting capacity



Material: Wood with nails  
Material: Wood with metal  
Product text, Accessories grey: **S 1122 VFR**  
Product text, Accessories grey: BIM, vario-pitched teeth  
Product text, Accessories grey: Pallets, cutting depth up to 165 mm, high flexibility  
SOL Date: 22.05.2013  
Novelty: no

Scope of delivery:  
5 ST Reciprocating saw blade S 1122 VFR. For reciprocating saws |

## PRODUCT DESCRIPTION

The S 1122 VFR Special for Pallet Repair Reciprocating Saw Blade is breakproof for continuous and effortless flush cuts in wood and metal. Its reverse tip prevents jamming, blade bending and shank breakage, enabling long life. The vario-tooth design reduces vibrations and allows for smooth cuts. Its standard gauge material (0.9 mm) and length provide excellent flush cuts. Made from BIM (bi-metal), the blades fully hardened HSS (high-speed steel) tooth strip is bonded with an elastic HCS (high carbon steel) blade, making it ideal for pallet repair applications. Its fine to medium vario-tooth pitch (1.8/2.6 mm) cuts through soft nails and fasteners in pallet construction. Its standard length of 225 mm cuts up to 165 mm deep.

Article ID: 2608658030

### PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.