



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH RECIPROCATING SAW BLADE S 1125 VFR. FOR RECIPROCATING SAWS

SKU: 3165140749367

Reciprocating saw blade S 1125 VFR. For reciprocating saws

Categories: [Accessories for BOSCH professional](#), [Saws](#)

Product Features: Pallets [mm]: 5-165

Tooth design: Vario toothing

Tooth spacing [mm]: 1.8-2.6

Tooth pitch [TPI]: 10-14

Total length [mm]: 225

Total length [Inch]: 9

Width [mm]: 19

Thickness [mm]: 1,25

Blade material: BI-METAL

Blade material abbreviation: BIM

Body material: HCS

Max. cut capacity [mm]: 165

Areas of application: Pallets, cutting depth up to 165 mm, maximum stability and lifetime

Progressive: no

Type: S 1125 VFR

Benefit HL (short): Breakproof Blade for Smooth Cuts

Performance Claim Text: Effortless Cuts (Version) Key RTB: Reverse tip prevents jamming, bending and shank breakage for long life

Specific RTB1: Vario-tooth design for vibration-reduced, smooth cuts

Specific RTB2: Thick gauge material for high stability. BIM blade is ideal for pallet repair applications

Specific RTB3: Fine to medium vario-tooth pitch cuts through soft nails and fasteners.

Standard length for a 165 mm cutting capacity



Material: Wood with hard nails
Material: Wood with tough metal
Material: Wood with metal
Product text, Accessories grey: **S 1125 VFR**
Product text, Accessories grey: BIM, vario-pitched teeth
Product text, Accessories grey: Pallets, cutting depth up to 165 mm, exceptional stability and lifetime
SOL Date: 01.07.2013
Novelty: no

Scope of delivery:
5 ST Reciprocating saw blade S 1125 VFR. For reciprocating saws |

PRODUCT DESCRIPTION

The S 1125 VFR Special for Pallet Repair Reciprocating Saw Blade is breakproof for continuous and effortless cuts in wood and metal. Its reverse tip prevents jamming, blade bending and shank breakage, enabling long life. The vario-tooth design reduces vibrations for smooth cuts. Its thick gauge material (1.25 mm) increases stability even further. Moreover, the blades BIM (bi-metal) fully hardened HSS (high-speed steel) tooth strip is bonded with an elastic HCS (high carbon steel) body, making it ideal for pallet repair applications. Its fine to medium vario-tooth pitch (1.8/2.6 mm) makes cuts through soft nails and fasteners in pallet construction. This reciprocating saw blade has a standard length of 225 mm for cutting up to 165 mm deep.

Article ID: 2608658036

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.