



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

ROBERT BOSCH POWER TOOLS GMBH RECIPROCATING SAW BLADE S 1210 VF. FOR RECIPROCATING SAWS

SKU: 3165140543378

Reciprocating saw blade S 1210 VF. For reciprocating saws



Categories: [Accessories for BOSCH professional](#), [Saws](#)

Product Features: Wood with nails/metal [mm]: <250

Wooden boards, chipboard [mm]: <250

Plastics: pipes, profiles [mm]: <250

Glass fibre reinforced plastic/epoxy [mm]: <250

Tooth design: special vario-pitched teeth for wood

Tooth spacing [mm]: 3.2-5.1

Tooth pitch [TPI]: 5-8

Total length [mm]: 300

Total length [Inch]: 12

Width [mm]: 22

Thickness [mm]: 1,6

Blade material: BI-METAL

Blade material abbreviation: BIM

Body material: HCS

Max. cut capacity [mm]: 250

Areas of application: Wood with nails/metal, wood, chipboard (<100 mm), glass fibre reinforced plastic/epoxy, solid (<50 mm), wall cutouts: wood+metal (<100 mm), for rescue/demolition work

Progressive: no

Type: S 1210 VF

Benefit HL (short): Fast Cuts for Demolition Work in Wood and Metal

Performance Claim Text: Fast Cuts for Demolition

(Version) Key RTB: Wide tapered body (22 mm) and extra-thick gauge material (1.6 mm)



for ultimate stability in demolition applications
Specific RTB1: Vario-tooth design/large gullets remove material efficiently for fast results
Specific RTB2: BIM blade material ideal for cutting regular-strength steel components embedded in wood
Specific RTB3: Long length of 300 mm for a cutting capacity of up to 250 mm
Material: Construction wood
Material: Plastics
Product text, Accessories grey: **S 1210 VF**
Product text, Accessories grey: BIM, special vario-pitched teeth for wood
Product text, Accessories grey: Wood with nails/metal, wood, chipboard (<250 mm), glass fibre reinforced plastic/epoxy, wall cutouts: wood+metal (<250 mm), for rescue/demolition work
SOL Date: 01.03.2009
Novelty: no

Scope of delivery:
5 ST Reciprocating saw blade S 1210 VF. For reciprocating saws |

PRODUCT DESCRIPTION

The S 1210 VF Heavy for Wood and Metal Reciprocating Saw Blade delivers fast cuts in wood and metal. Featuring a wide tapered body (22 mm) and extra-thick gauge material (1.6 mm), the blade sustains the ultimate stability needed for demolition applications and enables controlled straight cuts without bending. Its vario-tooth design and large gullets remove material efficiently, supporting fast work progress. Moreover, its BIM (bi-metal) base combines an HCS (high carbon steel) blade and an HSS (high-speed steel) tooth strip, which makes it ideal for cutting regular-strength steel components embedded in wood. The blade is equipped with a long length of 300 mm for a cutting capacity of up to 250 mm.

Article ID: 2608657612

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.