



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

ROBERT BOSCH POWER TOOLS GMBH RECIPROCATING SAW BLADE S 1222 VF. FOR RECIPROCATING SAWS

SKU: 3165140093453

Reciprocating saw blade S 1222 VF. For reciprocating saws



Categories: [Accessories for BOSCH professional](#), [Saws](#)

Product Features: Wood with nails/metal [mm]: <250

Sheet metal, pipes, profiles, from [mm]: 3

Sheet metal, pipes, profiles, to [mm]: 10

Sheet metals, pipes, profiles [mm]: 3-10

Glass fibre reinforced plastic/epoxy [mm]: <250

Tooth design: Vario toothing

Tooth spacing [mm]: 1.8-2.6

Tooth pitch [TPI]: 10-14

Total length [mm]: 300

Total length [Inch]: 12

Width [mm]: 19

Thickness [mm]: 0,9

Blade material: BI-METAL

Blade material abbreviation: BIM

Body material: HCS

Max. cut capacity [mm]: 250

Areas of application: Wood with nails/metal (<250 mm), sheet metals, aluminium profiles (3-10 mm), glass fibre reinforced

plastic/epoxy (<250 mm), flexible flush cut

Progressive: yes

Type: S 1222 VF

Benefit HL (short): Smooth Flush Cuts in Wood with Nails, Mild Steel and Non-Ferrous Metals

Performance Claim Text: Effortless Flush Cuts (Version) Key RTB: Vario-tooth geometry enables smooth and vibration-reduced cutting



Specific RTB1: Standard gauge material (0.9 mm) and long length provide ultimate flush-cutting capability

Specific RTB2: BIM blade is optimised to cut soft nails, mild steel materials and non-ferrous metal components embedded in wood

Specific RTB3: Long length (300 mm) for a cutting capacity of up to 250 mm

Material: Wood with nails

Material: Plastics

Product text, Accessories grey: **S 1222 VF**

Product text, Accessories grey: BIM, vario-pitched teeth

Product text, Accessories grey: Wood with nails/metal (<250 mm), sheet metals, aluminium profiles (3-10 mm), glass fibre reinforced plastic/epoxy (<250 mm), flexible flush cut

SOL Date: 19.07.2002

Novelty: no

Scope of delivery:

5 ST Reciprocating saw blade S 1222 VF. For reciprocating saws |

PRODUCT DESCRIPTION

The S 1222 VF Flexible for Wood and Metal Reciprocating Saw Blade delivers effortless flush cuts in wood and metal. Featuring a vario-tooth geometry, this reciprocating saw blade is ideal for smooth and vibration-reduced cutting. Moreover, its standard gauge material (0.9 mm) and long length provide ultimate flush-cutting capability. The BIM (bi-metal) blade is optimised to cut soft nails, mild steel materials and non-ferrous metal components embedded in wood. It is equipped with a long length (300 mm) for a cutting capacity up to 250 mm.

Article ID: 2608656043

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.