



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH RECIPROCATING SAW BLADE S 1227 BEF. FOR RECIPROCATING SAWS

SKU: 3165140836562

Reciprocating saw blade S 1227 BEF. For reciprocating saws

Categories: [Accessories for BOSCH professional](#), [Saws](#)

Product Features: Sheet metals, thick, from [mm]: 3

Sheet metals, thick, to [mm]: 8

Sheet metals, thick [mm]: 3-8

Pipes/profiles, thin-walled: open+closed [mm]: <250

Profiles, pipes: closed [mm]: <250

Profiles, pipes: open [mm]: <250

Tooth design: Micro Edge Geometry

Tooth spacing [mm]: 1.4+1.8

Tooth pitch [TPI]: 14+18

Total length [mm]: 300

Total length [Inch]: 12

Width [mm]: 25

Thickness [mm]: 1,1

Blade material: BI-METAL

Blade material abbreviation: BIM

Body material: HCS

Recommended min. material thickness [mm]: 2

Recommended max. material thickness [mm]: 6

Max. cut capacity [mm]: 250

Areas of application: Medium-thick to thick sheet metals (3-8 mm), thin-walled closed and open profiles and pipes (<250 mm). Fine, precise cuts at accurate angles

Progressive: no

Type: S 1227 BEF

Benefit HL (short): Precise and Smooth Cuts in Thin-Wall Metal Pipes and Profiles



Performance Claim Text: Precise and Smooth Cuts

(Version) Key RTB: Wide 25 mm body enables accurate cutting

Specific RTB1: Patented full-contact design with concave-shaped cutting edge increases lifetime and speed

Specific RTB2: Effortless work thanks to patented 2x2 fine tooth pitch geometry. BIM blade is designed for cutting steel materials

Specific RTB3: Tooth pitch (1.4+1.8 mm) for cutting thin-wall steel pipes and profiles.

Long length for a 250 mm cutting capacity

Material: Steel

Material: Stainless steel

Material: Cast iron

Material: Tough steel

Material: Metal pipes and profiles

Product text, Accessories grey: **S 1227 BEF**

Product text, Accessories grey: BIM, Micro Edge Geometry, patented 2x2 Tooth Geometry with Full Contact Design

Product text, Accessories grey: Medium-thick to thick sheet metals (2-6 mm), thin-walled closed and open profiles and pipes (<250 mm). Fine, precise cuts at accurate angles

SOL Date: 01.01.2016

Novelty: no

Scope of delivery:

5 ST Reciprocating saw blade S 1227 BEF. For reciprocating saws |

PRODUCT DESCRIPTION

The S 1227 BEF Endurance for Heavy Metal Reciprocating Saw Blade delivers precise and smooth straight cuts in metal. Its wide 25 mm body enables accurate cutting, while its patented full-contact design with a concave-shaped cutting edge increases the blades lifetime and speed. Moreover, work is effortless thanks to the blades patented 2x2 fine tooth pitch geometry. The BIM (bi-metal) blade is designed for cutting steel materials. Featuring a tooth pitch of 1.4+1.8 mm, this reciprocating saw blade can be used for cutting thin-wall steel pipes and profiles with a wall thickness of 3 mm to 8 mm. It is equipped with a long length of 300 mm, providing a cutting capacity of up to 250 mm.

Article ID: 2608658147

PRODUCT DATASHEET LEGAL NOTE



Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.