



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



**ROBERT BOSCH POWER TOOLS GMBH
RECIPROCATING SAW BLADE S 528 DF.
FOR RECIPROCATING SAWS**

SKU: 3165140612098

Reciprocating saw blade S 528 DF. For reciprocating saws

Categories: [Accessories for BOSCH professional, Saws](#)

Product Features: Plasterboard [mm]: <50
Fibre cement [mm]: <50
Tooth design: side set, milled
Tooth spacing [mm]: 4.3
Tooth pitch [TPI]: 6
Total length [mm]: 100
Total length [Inch]: 4
Width [mm]: 19
Thickness [mm]: 0,9
Blade material: BI-METAL
Blade material abbreviation: BIM
Body material: HCS
Max. cut capacity [mm]: 50
Areas of application: Plasterboard, Gypsum fibreboard (<50 mm), especially for plunge cuts, tear-free cuts
Progressive: no
Type: S 528 DF
Benefit HL (short): Clean Curved Cuts in Plasterboards
Performance Claim Text: Clean Curved Cuts (Version) Key RTB: Pointed teeth deliver tear-free results
Specific RTB1: Fully tapered body for easy access to hard-to-reach areas. Pointed tip for plunge cuts
Specific RTB2: BIM blade for cutting abrasive materials such as plasterboard
Specific RTB3: Short length of 100 mm for a cutting capacity of up to 50 mm. Ideal for use with cordless compact saws



Material: Drywall
Material: Fibre cement boards
Material: Drywall board
Product text, Accessories grey: **S 528 DF**
Product text, Accessories grey: BIM, side set, milled
Product text, Accessories grey: Especially optimised for use in compact saws.
Product text, Accessories grey: Plasterboard, Gypsum fibreboard (<50 mm), especially for plunge cuts, tear-free cuts
SOL Date: 01.04.2011
Novelty: no

Scope of delivery:
5 ST Reciprocating saw blade S 528 DF. For reciprocating saws |

PRODUCT DESCRIPTION

The S 528 DF Special for Plaster Reciprocating Saw Blade delivers clean curved and plunge cuts in special materials. Featuring pointed teeth, it delivers tear-free results, while its fully tapered body provides easy access to hard-to-reach areas. Moreover, a pointed tip makes the blade appropriate for plunge cuts. Made from BIM (bi-metal), the blades fully hardened HSS (high-speed steel) tooth strip is bonded with an elastic HCS (high carbon steel) blade, making it appropriate for cutting abrasive materials such as plasterboard. Its short length of 100 mm enables a cutting capacity of up to 50 mm.

Article ID: 2608657725

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.