



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH RECIPROCATING SAW BLADE S 610 VF. FOR RECIPROCATING SAWS

SKU: 3165140543347

Reciprocating saw blade S 610 VF. For reciprocating saws

Categories: [Accessories for BOSCH professional](#), [Saws](#)

Product Features: Wood with nails/metal [mm]: <100

Wooden boards, chipboard [mm]: <100

Plastics: pipes, profiles [mm]: <100

Glass fibre reinforced plastic/epoxy [mm]: <100

Tooth design: side set, milled

Tooth spacing [mm]: 3.2-5.1

Tooth pitch [TPI]: 5-8

Total length [mm]: 150

Total length [Inch]: 6

Width [mm]: 22

Thickness [mm]: 1,6

Blade material: BI-METAL

Blade material abbreviation: BIM

Body material: HCS

Max. cut capacity [mm]: 100

Areas of application: Wood with nails/metal, wood, chipboard (<100 mm), glass fibre reinforced plastic/epoxy, solid (<50 mm), wall cutouts: wood+metal (<100 mm), for rescue/demolition work

Progressive: no

Type: S 610 VF

Benefit HL (short): Fast Cuts for Demolition Work in Wood and Metal

Performance Claim Text: Fast Cuts for Demolition

(Version) Key RTB: Wide tapered body (22 mm) and extra-thick gauge material (1.6 mm) for ultimate stability in demolition



applications

Specific RTB1: Vario-tooth design and large gullets remove material efficiently for fast results

Specific RTB2: BIM blade material ideal for cutting regular-strength steel components embedded in wood

Specific RTB3: Standard length of 150 mm for a cutting capacity of up to 100 mm

Material: Construction wood

Material: Plastics

Product text, Accessories grey: **S 610 VF**

Product text, Accessories grey: BIM, special vario-pitched teeth for wood

Product text, Accessories grey: Wood with nails/metal, wood, chipboard (<100 mm), glass fibre reinforced plastic/epoxy, wall cutouts: wood+metal (<100 mm), for rescue/demolition work

SOL Date: 01.03.2009

Novelty: no

Scope of delivery:

5 ST Reciprocating saw blade S 610 VF. For reciprocating saws |

PRODUCT DESCRIPTION

The S 610 VF Heavy for Wood and Metal Reciprocating Saw Blade delivers fast straight cuts in wood and metal. Featuring a wide tapered body (22 mm) and extra-thick gauge material (1.6 mm), the blade sustains the ultimate stability needed for demolition applications, enabling controlled cuts without bending. Its vario-tooth design and large gullets remove material efficiently, supporting fast work progress. Made from BIM (bi-metal), the blades fully hardened HSS (high-speed steel) tooth strip is bonded with an elastic HCS (high carbon steel) blade, making it ideal for cutting regular-strength steel components embedded in wood. The blade is equipped with a standard length of 150 mm for a cutting capacity of up to 100 mm.

Article ID: 2608657608

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.