



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

## ROBERT BOSCH POWER TOOLS GMBH RECIPROCATING SAW BLADE S 611 DF. FOR RECIPROCATING SAWS

**SKU:** 3165140235518

Reciprocating saw blade S 611 DF. For reciprocating saws



**Categories:** [Accessories for BOSCH professional](#), [Saws](#)

**Product Features:** Wood with nails/metal [mm]: <100

Wooden boards, chipboard [mm]: <100

Plastics: pipes, profiles [mm]: <100

Glass fibre reinforced plastic/epoxy [mm]: <50

Tooth design: side set, milled

Tooth spacing [mm]: 4.3

Tooth pitch [TPI]: 6

Total length [mm]: 150

Total length [Inch]: 6

Width [mm]: 22

Thickness [mm]: 1,25

Blade material: BI-METAL

Blade material abbreviation: BIM

Body material: HCS

Max. cut capacity [mm]: 100

Areas of application: Wood with nails/metal, chipboard (<100 mm), plastic profiles (diameter <100 mm), plastics/glass fibre reinforced plastic, solid (<50 mm), window frames: wood + metal, especially for plunge cuts

Progressive: no

Type: S 611 DF

Benefit HL (short): Fast Cuts in Window Demolition

Performance Claim Text: Fast Cuts

(Version) Key RTB: Tooth pitch (4.3 mm) and side-set teeth for quick results

Specific RTB1: Fully tapered body allows easy



access to hard-to-reach areas  
Specific RTB2: Pointed tip designed for plunge cutting  
Specific RTB3: BIM blade is optimised for window demolition. Standard length (150 mm) provides a 100 mm cutting capacity  
Material: Wood with nails  
Material: Plastics  
Material: Aluminium  
Product text, Accessories grey: **S 611 DF**  
Product text, Accessories grey: BIM, side set, milled  
Product text, Accessories grey: Wood with nails/metal, chipboard (<100 mm), plastic profiles (<100 mm), glass fibre reinforced plastic/epoxy (<50 mm), window frames: wood + metal, especially for plunge cuts  
SOL Date: 19.07.2002  
Novelty: no

Scope of delivery:  
1 ST Reciprocating saw blade S 611 DF. For reciprocating saws |

## PRODUCT DESCRIPTION

The S 611 DF Heavy for Wood and Metal Reciprocating Saw Blade delivers fast plunge cuts in wood and metal. Its large tooth pitch (4.3 mm) and side-set teeth enable quick results in all common window stock dimensions. The reciprocating saw blades fully tapered body allows easy access to hard-to-reach areas, while its pointed tip is designed for plunge cutting. Moreover, its BIM (bi-metal) base combines an HCS (high carbon steel) blade and an HSS (high-speed steel) tooth strip, making it optimal for window demolition. It is equipped with a standard length of 150 mm, providing a cutting capacity of up to 100 mm.

Article ID: 2608656259

### PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.