Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH RECIPROCATING SAW BLADE S 628 DF. FOR RECIPROCATING SAWS

SKU: 3165140235891

Reciprocating saw blade S 628 DF. For reciprocating saws

Categories: Accessories for BOSCH professional, Saws

Product Features: Plasterboard [mm]: <100
Tooth design: side set, milled
Tooth spacing [mm]: 4.2
Tooth pitch [TPI]: 6
Total length [mm]: 150
Total length [Inch]: 6
Width [mm]: 19
Thickness [mm]: 1,25
Blade material: BI-METAL
Blade material abbreviation: BIM
Body material: HCS
Max. cut capacity [mm]: 100
Areas of application: Plasterboard (<100 mm), especially for plunge cut, tear-free cut
Progressive: no
Type: S 628 DF
Benefit HL (short): Clean Curved Cuts in Plasterboard
Performance Claim Text: Clean Curved Cuts (Version) Key RTB: Pointed teeth deliver tear-free results
Specific RTB1: Fully tapered body for easy access to hard-to-reach areas and curved cuts. Pointed tip enables plunge cuts
Specific RTB2: BIM blade for cutting abrasive materials such as plasterboard
Specific RTB3: Standard length of 150 mm for a cutting capacity of up to 100 mm. Ideal for use with cordless compact saws
Material: Drywall board
Product text, Accessories grey: **S 628 DF**

Copyright © 2023 Actik Tools All rights reserved

Product text, Accessories grey: BIM, side set, milled
Product text, Accessories grey: Plasterboard, Gypsum fibreboard (<100 mm), especially for plunge cuts, tear-free cuts
SOL Date: 19.07.2002
Novelty: no

Scope of delivery:
5 ST Reciprocating saw blade S 628 DF. For reciprocating saws |

PRODUCT DESCRIPTION

The S 628 DF Special for Plaster Reciprocating Saw Blade delivers clean curved cuts in special materials. Featuring pointed teeth, it delivers tear-free results, while its fully tapered body provides easy access to hard-to-reach areas and enables curved cuts. Moreover, a pointed tip makes the blade appropriate for plunge cuts. Made from BIM (bi-metal), the blades fully hardened HSS (high-speed steel) tooth strip is bonded with an elastic HCS (high carbon steel) blade, making it appropriate for cutting abrasive materials such as plasterboard. Its standard length of 150 mm enables a cutting capacity of up to 100 mm.

Article ID: 2608656274

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.

Copyright © 2023 Actik Tools All rights reserved