




Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



## ROBERT BOSCH POWER TOOLS GMBH RECIPROCATING SAW BLADE S 644 D. FOR RECIPROCATING SAWS

**SKU:** 3165140016025

Reciprocating saw blade S 644 D. For reciprocating saws

---

**Categories:** [Accessories for BOSCH professional](#), [Saws](#)

**Product Features:** Construction wood [mm]: <100

Boards [mm]: 6-60

Wooden wall cutout [mm]: <100

Plastic [mm]: <100

Tooth design: side set, ground

Tooth spacing [mm]: 4

Tooth pitch [TPI]: 6

Total length [mm]: 150

Total length [Inch]: 6

Width [mm]: 19

Thickness [mm]: 1,25

Blade material: HighCarbonSteel

Blade material abbreviation: HCS

Body material: HCS

Max. cut capacity [mm]: 100

Areas of application: Construction wood (<100 mm), wooden wall (<100 mm), boards: chipboard, MDF (6-60 mm), plywood, plastic (<100 mm), especially for plunge cuts

Progressive: no

Type: S 644 D

Benefit HL (short): Clean Curved Cuts in Construction Materials

Performance Claim Text: Clean Curved Cuts (Version) Key RTB: Sharp-ground teeth enable tear-free cuts

Specific RTB1: Fully tapered body provides easy access to hard-to-reach areas and enables curved cutting. Pointed tip for plunge cuts



Specific RTB2: HCS blade material for cutting wood and non-abrasive woodworking materials in construction applications

Specific RTB3: Standard length of 150 mm for a 100 mm cutting capacity

Material: Construction wood

Product text, Accessories grey: **S 644 D**

Product text, Accessories grey: HCS, side set, ground

Product text, Accessories grey: Construction wood (<100 mm), wooden wall (<100 mm), boards: chipboard, MDF (6-60 mm), plywood, plastic (<100 mm), especially for plunge cuts

SOL Date: 19.07.2002

Novelty: no

Scope of delivery:

5 ST Reciprocating saw blade S 644 D. For reciprocating saws |

## PRODUCT DESCRIPTION

The S 644 D Top for Wood Reciprocating Saw Blade delivers clean curved and plunge cuts in wood. Its sharp-ground teeth enable tear-free cuts. Additionally, the blades fully tapered body provides easy access to hard-to-reach areas and makes curved cutting possible. Featuring a pointed tip, the blade is specially designed for plunge cuts. It is made of HCS (high carbon steel), which makes it appropriate for cutting soft wood, construction wood and all non-abrasive woodworking materials in construction applications. It has a standard length of 150 mm, which enables a cutting capacity of up to 100 mm.

Article ID: 2608650673

### PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.