



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH RECIPROCATING SAW BLADE S 927 BEF. FOR RECIPROCATING SAWS

SKU: 3165140507158

Reciprocating saw blade S 927 BEF. For reciprocating saws

Categories: <u>Accessories for BOSCH</u> professional, <u>Saws</u>

Product Features: Sheet metals, thick, from [mm]: 3 Sheet metals, thick, to [mm]: 8 Sheet metals, thick [mm]: 3-8 Pipes/profiles, thin-walled: open+closed [mm]: <100 Profiles, pipes: closed [mm]: <100 Profiles, pipes: open [mm]: <100 Tooth design: Micro Edge Geometry Tooth spacing [mm]: 1.4+1.8 Tooth pitch [TPI]: 14+18 Total length [mm]: 150 Total length [Inch]: 6 Width [mm]: 25 Thickness [mm]: 1,1 Blade material: BI-METAL Blade material abbreviation: BIM Body material: HCS Recommended min. material thickness [mm]: 2 Recommended max. material thickness [mm]: 6 Max. cut capacity [mm]: 100 Areas of application: Medium-thick to thick sheet metals (3-8 mm), thin-walled closed and open profiles and pipes (<100 mm). Fine, precise cuts at accurate angles. Progressive: no Type: S 936 BEF Benefit HL (short): Precise and Smooth Cuts in Thin-Wall Metal Pipes and Profiles





Performance Claim Text: Precise and Smooth Cuts (Version) Key RTB: Wide 25 mm body enables accurate straight cutting Specific RTB1: Patented full-contact design with concave-shaped cutting edge increases lifetime and speed Specific RTB2: Effortless work thanks to patented 2x2 fine tooth pitch geometry. BIM blade is designed for cutting steel materials Specific RTB3: Tooth pitch (1.4+1.8 mm) for cutting thin-wall steel pipes and profiles. Standard length for a 100 mm cutting capacity Material: Steel Material: Stainless steel Material: Cast iron Material: Tough steel Material: Metal pipes and profiles Product text, Accessories grey: S 927 BEF Product text, Accessories grey: BIM, Micro Edge Geometry, patented 2x2 Tooth Geometry with Full Contact Design Product text, Accessories grey: Medium-thick to thick sheet metals (2-6 mm), thin-walled closed and open profiles and pipes (<100 mm). Fine, precise cuts at accurate angles. SOL Date: 01.01.2016 Novelty: no

Scope of delivery: 5 ST Reciprocating saw blade S 927 BEF. For reciprocating saws |

PRODUCT DESCRIPTION

The S 927 BEF Speed for Heavy Metal Reciprocating Saw Blade delivers precise and smooth straight cuts in metal. Its wide 25 mm body enables accurate straight cutting, while its patented full-contact design with a concave-shaped cutting edge increases the blades lifetime and speed. Moreover, work is effortless thanks to its patented 2x2 fine tooth pitch geometry. The BIM (bi-metal) blade is designed for cutting steel materials. Featuring a tooth pitch of 1.4+1.8 mm, this reciprocating saw blade can be used for cutting thin-wall steel pipes and profiles with a wall thickness of 3 mm to 8 mm. It is equipped with a standard length of 150 mm, providing a cutting capacity of up to 100 mm.

Article ID: 2608657523





PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.