Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH ROTARY HAMMER WITH SDS MAX GBH 12-52 D

SKU: 3165140604307

Rotary Hammer with SDS max GBH 12-52 D

Categories: BOSCH professional, Drill & percussion hammers

Product Features: Vibration emission value ah [Hammer drilling in concrete]: 1,5 m/s²
Uncertainty K [Hammer drilling in concrete]: 20,0 m/s²
Vibration emission value ah [Chiselling in concrete]: 2,8 m/s²
Uncertainty K [Chiselling in concrete]: 15,0 m/s²
Packaging dimensions (width): 502 mm
Packaging dimensions (length): 679 mm
Packaging dimensions (height): 151 mm
Packaging dimensions (width x length x height): 502 x 679 x 151 mm
Voltage, electrical: 230 V
Rated input power: 1.700 W
Impact energy (according to EPTA 05/2016): 19 J
Impact rate at rated speed, from: 1.750 bpm
Impact rate at rated speed, up to: 2.150 bpm
Impact rate at rated speed: 1,750 - 2,150 bpm
Rated speed, from: 0 rpm
Rated speed, up to: 220 rpm
Rated speed: 0 - 220 rpm
Weight: 11,5 kg
Tool dimensions (width): 120 mm
Tool dimensions (length): 600 mm
Tool dimensions (height): 312 mm
Tool holder: SDS max
Drilling dia. concrete, hammer drill bits, from: 12 mm
Drilling dia. concrete, hammer drill bits, up to: 52 mm

Copyright © 2023 Actik Tools All rights reserved

Drilling dia. concrete, hammer drill bits: 12 - 52 mm
Rec. appl. range concrete, hammer drill bits, from: 30 mm
Rec. appl. range concrete, hammer drill bits, to: 50 mm
Opt. appl. range concrete, hammer drill bits: 30 - 50 mm
Min. dia. in concrete with breakthrough drill bits: 80 mm
Max. dia. in concrete with breakthrough drill bits: 80 mm
Drilling dia. concrete, breakthrough drill bits: 80 - 80 mm
Min. dia. in concrete with core cutters: 50 mm
Max. dia. in concrete with core cutters: 150 mm
Drilling diameter in concrete with core cutters: 50 - 150 mm
Product category subdivision: Rotary Hammer with SDS max
Positioning: Boschs most heavy-duty SDS max rotary hammer
User benefit incl. Reason to believe: High-end motor for ultimate performance in SDS max tasks
User benefit incl. Reason to believe: Powerful motor enables the delivery of 19 J of impact energy for heavy chiselling
User benefit incl. Reason to believe: Highly durable due to extremely robust metal components
Positioning (BE): The most powerful rotary hammer from Bosch!
User benefit incl. Reason to believe (BE): Top performance when drilling and chiselling thanks to the 1.700 watt motor and 19 joules of single impact energy
User benefit incl. Reason to believe (BE): Exceptional durability thanks to robust metal components
User benefit incl. Reason to believe (BE): Automatic lock-on switch for highest user comfort during continuous chiselling applications
Areas of application: Drilling in concrete
Areas of application: Drilling in stone

Copyright © 2023 Actik Tools All rights reserved

Areas of application: Chiselling in concrete
Areas of application: Chiselling in natural materials
Areas of application: Chiselling in stone
Title: Rotary Hammer with SDS max GBH 12-52 D Professional
Novelty: no
Scope of supply: Auxiliary handle (spare part number 1 612 025 004)
Scope of supply: Grease tube (spare part number 1 615 430 010)
Scope of supply: Machine cloth
Scope of supply: Carrying case (spare part number 1 615 438 705)
SOL Date: 01.06.2015

Scope of delivery:
1 ST Rotary Hammer with SDS max GBH 12-52 D |

PRODUCT DESCRIPTION

Rotary Hammer with SDS max GBH 12-52 D, The GBH 12-52 D Professional is the most heavy-duty tool in Boschs SDS max corded rotary hammer range. It features a high-end motor producing the ultimate performance in SDS max applications. The rotary hammers incredibly powerful motor enables the delivery of 19 J of impact energy, perfect for tough chiselling. It is also designed for high durability, featuring extremely robust metal components. This tool is intended for drilling up to 52 mm in diameter and heavy chiselling work in concrete and stone. It is compatible with various dust attachments. The GBH 12-52 D Professional features include Constant Speed, Restart Protection, Rotation Control Clutch, and Speed Selection. Auxiliary handle (spare part number 1 612 025 004); Grease tube (spare part number 1 615 430 010); Machine cloth; Carrying case (spare part number 1 615 438 705)

Article ID: 0611266100

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.

Copyright © 2023 Actik Tools All rights reserved