Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH ROTARY HAMMER WITH SDS MAX GBH 5-40 DCE

SKU: 3165140461214

Rotary Hammer with SDS max GBH 5-40 DCE

Categories: BOSCH professional, Drill & percussion hammers

Product Features: Tool dimensions (length): 485 mm
Tool dimensions (height): 260 mm
Tool holder: SDS max
Packaging dimensions (width): 410 mm
Packaging dimensions (length): 615 mm
Packaging dimensions (height): 145 mm
Packaging dimensions (width x length x height): 410 x 615 x 145 mm
Voltage, electrical: 230 V
Rated input power: 1.150 W
Impact energy (according to EPTA 05/2016): 8,8 J
Impact rate at rated speed, from: 1.500 bpm
Impact rate at rated speed, up to: 3.050 bpm
Impact rate at rated speed: 1,500 - 3,050 bpm
Rated speed, from: 170 rpm
Rated speed, up to: 340 rpm
Rated speed: 170 - 340 rpm
Weight: 6,8 kg
Drilling dia. concrete, hammer drill bits, from: 12 mm
Drilling dia. concrete, hammer drill bits, up to: 40 mm
Drilling dia. concrete, hammer drill bits: 12 - 40 mm
Rec. appl. range concrete, hammer drill bits, from: 18 mm
Rec. appl. range concrete, hammer drill bits, to: 32 mm
Opt. appl. range concrete, hammer drill bits: 18 - 32 mm

Copyright © 2023 Actik Tools All rights reserved

Min. dia. in concrete with breakthrough drill bits: 45 mm
Max. dia. in concrete with breakthrough drill bits: 55 mm
Drilling dia. concrete, breakthrough drill bits: 45 - 55 mm
Min. dia. in concrete with core cutters: 40 mm
Max. dia. in concrete with core cutters: 90 mm
Drilling diameter in concrete with core cutters: 40 - 90 mm
Product category subdivision: Rotary Hammer with SDS max
Positioning: Boschs SDS max rotary hammer for comfortable handling in extensive applications
User benefit incl. Reason to believe: Vibration Control and lightweight design for effortless and continuous work in time-intensive applications
User benefit incl. Reason to believe: Durable due to robust metal components and optimised lubrication system
User benefit incl. Reason to believe: Powerful motor enables the delivery of 8.8 J of impact energy for fast drilling and high removal rate
Positioning (BE): The fast all-rounder with Vibration Control
User benefit incl. Reason to believe (BE): Fastest drilling rate in its class due to 1150 W motor and powerful hammer mechanism
User benefit incl. Reason to believe (BE): SDS max comfort for easy and fast tool changes with one hand
User benefit incl. Reason to believe (BE): Vibration Control (10 m/s^2 for drilling, 8 m/s^2 for chiselling) ensures convenient working, even in time-intensive applications
Areas of application: Drilling in concrete
Areas of application: Drilling in stone
Areas of application: Chiselling in concrete
Areas of application: Chiselling in natural materials
Areas of application: Chiselling in stone
Title: Rotary Hammer with SDS max GBH 5-40 DCE Professional
Novelty: no

Copyright © 2023 Actik Tools All rights reserved

Scope of supply: Auxiliary handle (2 602 025 117)
Scope of supply: Grease tube (spare part number 1 615 430 010)
Scope of supply: Machine cloth
Scope of supply: Carrying case (1 615 438 461)
SOL Date: 01.10.2008

Scope of delivery:
1 ST Rotary Hammer with SDS max GBH 5-40 DCE |

PRODUCT DESCRIPTION

Rotary Hammer with SDS max GBH 5-40 DCE, The GBH 5-40 DCE Professional is uniquely designed within Boschs SDS max corded rotary hammer category for comfortable handling and reduced user fatigue in extensive applications. Its Vibration Control and lightweight design enable effortless and continuous work in time-intensive tasks. The rotary hammer is also built for durability, featuring robust metal components and an optimised lubrication system. Its strong motor enables the delivery of 8.8 J of impact energy for a fast drilling progress and high material removal rate. This tool is intended for drilling up to 40 mm in diameter and light chiselling work in concrete and stone. It is compatible with various dust attachments. The GBH 5-40 DCE Professional also features Constant Speed, Rotation Control Clutch, and Speed Selection. Auxiliary handle (2 602 025 117); Grease tube (spare part number 1 615 430 010); Machine cloth; Carrying case (1 615 438 461)

Article ID: 0611264000

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.

Copyright © 2023 Actik Tools All rights reserved