



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



## ROBERT BOSCH POWER TOOLS GMBH ROTARY HAMMER WITH SDS PLUS GBH 2-26 F

**SKU:** 3165140859202

Rotary Hammer with SDS plus GBH 2-26 F

**Categories:** [BOSCH professional](#), [Drill & percussion hammers](#)

**Product Features:** Scope of supply: Carrying case

Scope of supply: Depth stop 210 mm (1 613 001 010)

Scope of supply: Machine cloth

Scope of supply: Quick change chuck 13 mm (2 608 572 212)

Scope of supply: SDS plus quick-change chuck (2 608 572 213)

SOL Date: 01.09.2016

Packaging dimensions (width): 360 mm

Packaging dimensions (length): 446 mm

Packaging dimensions (height): 116 mm

Packaging dimensions (width x length x height): 360 x 446 x 116 mm

Voltage, electrical: 230 V

Rated input power: 830 W

Impact energy (according to EPTA 05/2016): 2,7 J

Impact rate at rated speed, from: 0 bpm

Impact rate at rated speed, up to: 4.000 bpm

Impact rate at rated speed: 0 - 4,000 bpm

Rated speed, from: 0 rpm

Rated speed, up to: 900 rpm

Rated speed: 0 - 900 rpm

Weight: 2,9 kg

Tool dimensions (width): 83 mm

Tool dimensions (length): 407 mm

Tool dimensions (height): 210 mm

Tool holder: SDS plus

Drilling dia. concrete, hammer drill bits, from: 4 mm



Drilling dia. concrete, hammer drill bits, up to: 26 mm

Drilling dia. concrete, hammer drill bits: 4 - 26 mm

Rec. appl. range concrete, hammer drill bits, from: 8 mm

Rec. appl. range concrete, hammer drill bits, to: 16 mm

Opt. appl. range concrete, hammer drill bits: 8 - 16 mm

Min. dia. in concrete with core cutters: 16 mm

Max. dia. in concrete with core cutters: 68 mm

Drilling diameter in concrete with core cutters: 16 - 68 mm

Max. drilling diameter masonry, core cutters: 68 mm

Max. drilling diameter in metal: 13 mm

Max. drilling diameter in wood: 30 mm

Product category subdivision: Rotary Hammer with SDS plus

Positioning: All-round performance rotary hammer with quick-change chuck in the SDS plus category

User benefit incl. Reason to believe: Delivers 2.7 J of impact energy for fast drilling and high chisel removal performance

User benefit incl. Reason to believe: High-quality components ensure robustness, reliability, and long lifetime

User benefit incl. Reason to believe: Optional chisel mode and quick-change chuck enable use in wide range of applications

Positioning (BE): Fast all-rounder for daily use

User benefit incl. Reason to believe (BE):

Improved performance for a fast drilling rate and high chiselling removal rate

User benefit incl. Reason to believe (BE):

Reliable and robust with long lifetime due to high-quality components

User benefit incl. Reason to believe (BE): Wide range of applications for drilling, hammer drilling and chiselling

Areas of application: Drilling in concrete

Areas of application: Drilling in ferrous metals

Areas of application: Drilling in wood

Areas of application: Drilling in synthetic



material

Areas of application: Drilling in stone

Areas of application: Chiselling in concrete

Areas of application: Chiselling in wood

Areas of application: Chiselling in stone

Title: Rotary Hammer with SDS plus GBH 2-26 F Professional

Novelty: no

Scope of supply: Auxiliary handle (2 602 025 141)

Scope of delivery:

1 ST Rotary Hammer with SDS plus GBH 2-26

F |

## PRODUCT DESCRIPTION

Rotary Hammer with SDS plus GBH 2-26 F, The GBH 2-26 F Professional with a quick-change chuck is the all-round performer in Bosch's SDS plus corded rotary hammer category, and is the perfect tool for daily use. Its strong motor delivers 2.7 J of impact energy, providing fast drilling and high chisel removal performance. Reliable and robust, the rotary hammers high-quality components also ensure a long lifetime. Its optional chisel mode and quick-change chuck enable use in a wide range of applications. This tool is intended for drilling and chiselling in concrete, masonry, wood, and metal. It is compatible with various dust attachments. The GBH 2-26 F Professional also includes features such as Reverse Mode, Rotation Control Clutch, Variable Speed, and Vario-Lock. Auxiliary handle (2 602 025 141); Carrying case; Depth stop 210 mm (1 613 001 010); Machine cloth; Quick change chuck 13 mm (2 608 572 212); SDS plus quick-change chuck (2 608 572 213)

Article ID: 06112A4000

### PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.