Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH ROTARY HAMMER WITH SDS PLUS GBH 2-28 F

SKU: 3165140843669

Rotary Hammer with SDS plus GBH 2-28 F

Categories: BOSCH professional, Drill & percussion hammers

Product Features: Tool dimensions (height): 216 mm
Max. dia. in concrete with core cutters: 68 mm
Drilling diameter in concrete with core cutters: 68 mm
Packaging dimensions (width): 365 mm
Packaging dimensions (length): 445 mm
Packaging dimensions (height): 155 mm
Packaging dimensions (width x length x height): 365 x 445 x 155 mm
Voltage, electrical: 230 V
Rated input power: 880 W
Impact energy (according to EPTA 05/2016): 3,2 J
Impact rate at rated speed, from: 0 bpm
Impact rate at rated speed, up to: 4.000 bpm
Impact rate at rated speed: 0 - 4,000 bpm
Rated speed, from: 0 rpm
Rated speed, up to: 900 rpm
Rated speed: 0 - 900 rpm
Weight: 3,1 kg
Tool dimensions (width): 402 mm
Tool dimensions (length): 216 mm
Tool holder: SDS plus
Drilling dia. concrete, hammer drill bits, from: 4 mm
Drilling dia. concrete, hammer drill bits, up to: 28 mm
Drilling dia. concrete, hammer drill bits: 4 - 28 mm
Rec. appl. range concrete, hammer drill bits,

Copyright © 2023 Actik Tools All rights reserved

from: 8 mm
Rec. appl. range concrete, hammer drill bits, to: 16 mm
Opt. appl. range concrete, hammer drill bits: 8 - 16 mm
Max. drilling diameter masonry, core cutters: 68 mm
Max. drilling diameter in metal: 13 mm
Max. drilling diameter in wood: 30 mm
Product category subdivision: Rotary Hammer with SDS plus
Positioning: Strongest rotary hammer in Bosch 2 kg SDS plus category with quick-change chuck
User benefit incl. Reason to believe: Delivers 3.2 J of impact energy for high-power drilling performance
User benefit incl. Reason to believe: KickBack Control for increased user protection
User benefit incl. Reason to believe: Vibration Control for effortless and continuous work in time-intensive applications
Positioning (BE): Top performance with intelligent KickBack Control
User benefit incl. Reason to believe (BE): Best performance in its class with improved power
User benefit incl. Reason to believe (BE): Increased user protection with KickBack Control (KBC) in order to minimise the risk of injury
User benefit incl. Reason to believe (BE): Active vibration damping with counter oscillator for minimal vibration levels
Areas of application: Drilling in concrete
Areas of application: Drilling in ferrous metals
Areas of application: Drilling in wood
Areas of application: Drilling in synthetic material
Areas of application: Drilling in stone
Areas of application: Chiselling in concrete
Areas of application: Chiselling in wood
Areas of application: Chiselling in stone
Areas of application: Screwdriving
Title: Rotary Hammer with SDS plus GBH 2-28 F Professional
Novelty: no
Novelty until: 01.12.2016
Scope of supply: Auxiliary handle (2 602 025

Copyright © 2023 Actik Tools All rights reserved

141)
Scope of supply: Depth stop 210 mm (1 613 001 010)
Scope of supply: L-BOXX inlay
Scope of supply: L-BOXX 136 (1 600 A01 2G0)
Scope of supply: Machine cloth
Scope of supply: Quick change chuck 13 mm (2 608 572 212)
Scope of supply: SDS plus quick-change chuck (2 608 572 213)
SOL Date: 29.08.2016

Scope of delivery:
1 ST Rotary Hammer with SDS plus GBH 2-28 F |

PRODUCT DESCRIPTION

Rotary Hammer with SDS plus GBH 2-28 F, The GBH 2-28 F Professional with a quick-change chuck is the strongest tool within the Bosch 2 kg SDS plus corded rotary hammer category. Its robust motor delivers an outstanding 3.2 J of impact energy for high-power drilling performance. The rotary hammer also features KickBack Control for increased user protection and Vibration Control for effortless and continuous work in time-intensive applications. This tool is intended for drilling and chiselling in concrete, masonry, wood, and metal. It is compatible with various dust attachments. The GBH 2-28 F Professional also features Reverse Mode, Rotation Control Clutch, Variable Speed, and Vario-Lock. Auxiliary handle (2 602 025 141); Depth stop 210 mm (1 613 001 010); L-BOXX inlay; L-BOXX 136 (1 600 A01 2G0); Machine cloth; Quick change chuck 13 mm (2 608 572 212); SDS plus quick-change chuck (2 608 572 213)

Article ID: 0611267601

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.

Copyright © 2023 Actik Tools All rights reserved