



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



## ROBERT BOSCH POWER TOOLS GMBH ROTARY HAMMER WITH SDS PLUS GBH 2-28 F

SKU: 3165140843652

Rotary Hammer with SDS plus GBH 2-28 F

**Categories:** [BOSCH professional](#), [Drill & percussion hammers](#)

**Product Features:** Tool dimensions (height):

216 mm

Max. dia. in concrete with core cutters: 68 mm

Drilling diameter in concrete with core cutters: 68 mm

Packaging dimensions (width): 360 mm

Packaging dimensions (length): 446 mm

Packaging dimensions (height): 113 mm

Packaging dimensions (width x length x height): 360 x 446 x 113 mm

Voltage, electrical: 230 V

Rated input power: 880 W

Impact energy (according to EPTA 05/2016): 3,2 J

Impact rate at rated speed, from: 0 bpm

Impact rate at rated speed, up to: 4.000 bpm

Impact rate at rated speed: 0 - 4,000 bpm

Rated speed, from: 0 rpm

Rated speed, up to: 900 rpm

Rated speed: 0 - 900 rpm

Weight: 3,1 kg

Tool dimensions (width): 402 mm

Tool dimensions (length): 216 mm

Tool holder: SDS plus

Drilling dia. concrete, hammer drill bits, from: 4 mm

Drilling dia. concrete, hammer drill bits, up to: 28 mm

Drilling dia. concrete, hammer drill bits: 4 - 28 mm

Rec. appl. range concrete, hammer drill bits,



from: 8 mm  
Rec. appl. range concrete, hammer drill bits,  
to: 16 mm  
Opt. appl. range concrete, hammer drill bits:  
8 - 16 mm  
Max. drilling diameter masonry, core cutters:  
68 mm  
Max. drilling diameter in metal: 13 mm  
Max. drilling diameter in wood: 30 mm  
Product category subdivision: Rotary  
Hammer with SDS plus  
Positioning: Strongest rotary hammer in  
Bosch 2 kg SDS plus category with quick-  
change chuck  
User benefit incl. Reason to believe: Delivers  
3.2 J of impact energy for high-power drilling  
performance  
User benefit incl. Reason to believe: KickBack  
Control for increased user protection  
User benefit incl. Reason to believe: Vibration  
Control for effortless and continuous work in  
time-intensive applications  
Positioning (BE): Top performance with  
intelligent KickBack Control  
User benefit incl. Reason to believe (BE): Best  
performance in its class with improved power  
User benefit incl. Reason to believe (BE):  
Increased user protection with KickBack  
Control (KBC) in order to minimise the risk of  
injury  
User benefit incl. Reason to believe (BE):  
Active vibration damping with counter  
oscillator for minimal vibration levels  
Areas of application: Drilling in concrete  
Areas of application: Drilling in ferrous metals  
Areas of application: Drilling in wood  
Areas of application: Drilling in synthetic  
material  
Areas of application: Drilling in stone  
Areas of application: Chiselling in concrete  
Areas of application: Chiselling in wood  
Areas of application: Chiselling in stone  
Areas of application: Screwdriving  
Title: Rotary Hammer with SDS plus GBH 2-28  
F Professional  
Novelty: no  
Novelty until: 01.12.2016  
Scope of supply: Auxiliary handle (2 602 025



141)

Scope of supply: Carrying case

Scope of supply: Depth stop 210 mm (1 613 001 010)

Scope of supply: Machine cloth

Scope of supply: Quick change chuck 13 mm (2 608 572 212)

Scope of supply: SDS plus quick-change chuck (2 608 572 213)

SOL Date: 29.08.2016

Scope of delivery:

1 ST Rotary Hammer with SDS plus GBH 2-28 F |

## PRODUCT DESCRIPTION

Rotary Hammer with SDS plus GBH 2-28 F, The GBH 2-28 F Professional with a quick-change chuck is the strongest tool within the Bosch 2 kg SDS plus corded rotary hammer category. Its robust motor delivers an outstanding 3.2 J of impact energy for high-power drilling performance. The rotary hammer also features KickBack Control for increased user protection and Vibration Control for effortless and continuous work in time-intensive applications. This tool is intended for drilling and chiselling in concrete, masonry, wood, and metal. It is compatible with various dust attachments. The GBH 2-28 F Professional also features Reverse Mode, Rotation Control Clutch, Variable Speed, and Vario-Lock. Auxiliary handle (2 602 025 141); Carrying case; Depth stop 210 mm (1 613 001 010); Machine cloth; Quick change chuck 13 mm (2 608 572 212); SDS plus quick-change chuck (2 608 572 213)

Article ID: 0611267600

### PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.