



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



## ROBERT BOSCH POWER TOOLS GMBH ROTARY HAMMER WITH SDS PLUS GBH 4-32 DFR

**SKU:** 3165140463096

Rotary Hammer with SDS plus GBH 4-32 DFR

---

**Categories:** [BOSCH professional](#), [Drill & percussion hammers](#)

**Product Features:** Rated speed, from: 0 rpm  
Rated speed, up to: 800 rpm  
Rated speed: 0 - 800 rpm  
Packaging dimensions (width): 365 mm  
Packaging dimensions (length): 475 mm  
Packaging dimensions (height): 127 mm  
Packaging dimensions (width x length x height): 365 x 475 x 127 mm  
Voltage, electrical: 230 V  
Rated input power: 900 W  
Impact energy (according to EPTA 05/2016): 4,2 J  
Impact rate at rated speed, from: 0 bpm  
Impact rate at rated speed, up to: 3.600 bpm  
Impact rate at rated speed: 0 - 3,600 bpm  
Weight: 4,7 kg  
Tool dimensions (width): 377 mm  
Tool dimensions (length): 493 mm  
Tool dimensions (height): 133 mm  
Tool holder: SDS plus  
Drilling dia. concrete, hammer drill bits, from: 6 mm  
Drilling dia. concrete, hammer drill bits, up to: 32 mm  
Drilling dia. concrete, hammer drill bits: 6 - 32 mm  
Rec. appl. range concrete, hammer drill bits, from: 14 mm  
Rec. appl. range concrete, hammer drill bits, to: 25 mm  
Opt. appl. range concrete, hammer drill bits: 14 - 25 mm



Max. drilling diameter masonry, core cutters:  
90 mm

Max. drilling diameter in metal: 13 mm

Max. drilling diameter in wood: 32 mm

Product category subdivision: Rotary  
Hammer with SDS plus

Positioning: Robustness combined with  
durability and excellent performance in the  
SDS plus category

User benefit incl. Reason to believe: 900 W  
motor delivers 4.2 J of impact energy for very  
fast chisel removal rates

User benefit incl. Reason to believe: Durable  
due to robust metal gearbox housing design

User benefit incl. Reason to believe: Vibration  
Control for effortless and continuous work in  
time-intensive applications

Positioning (BE): The fastest multi-hammer in  
the 4kg class

User benefit incl. Reason to believe (BE): Wide  
range of applications in chiselling and drilling  
work and when working with a core cutter

User benefit incl. Reason to believe (BE):  
Drills up to 30% faster (25 mm diameter) than  
other tools in its class

User benefit incl. Reason to believe (BE): Low  
vibration levels of only 12 m/s<sup>2</sup> for less tiring  
work due to Bosch Vibration Control

Areas of application: Drilling in concrete

Areas of application: Drilling in ferrous metals

Areas of application: Drilling in wood

Areas of application: Drilling in synthetic  
material

Areas of application: Drilling in non-ferrous  
metal

Areas of application: Drilling in stone

Areas of application: Dry drilling in stone

Areas of application: Chiselling in concrete

Areas of application: Chiselling in wood

Areas of application: Chiselling in stone

Areas of application: Screwdriving

Title: Rotary Hammer with SDS plus GBH 4-32  
DFR Professional

Novelty: no

Scope of supply: Depth stop 310 mm (1 613  
001 003)

Scope of supply: Machine cloth

Scope of supply: Carrying case (2 605 438)



651)

Scope of supply: Quick change chuck 13 mm  
(2 608 572 212)

Scope of supply: SDS plus quick-change  
chuck (2 608 572 213)

Scope of supply: Auxiliary handle (2 602 025  
176)

Scope of supply: Grease tube (spare part  
number 1 615 430 010)

SOL Date: 01.07.2009

Scope of delivery:

1 ST Rotary Hammer with SDS plus GBH 4-32  
DFR |

## PRODUCT DESCRIPTION

Rotary Hammer with SDS plus GBH 4-32 DFR, The powerful GBH 4-32 DFR Professional with SDS plus delivers 4.2 J of impact energy with an 900 W motor for a very fast chisel removal rate. The rotary hammer is designed for durability, featuring a very robust metal gearbox housing. Its Vibration Control enables effortless and continuous work in time intensive applications. This rotary hammer is intended for drilling and chiselling in concrete, masonry, wood, and metal. It is compatible with various dust attachments. The GBH 4-32 DFR Professional also features a keyless and quick-change chuck, Reverse Mode, Rotation Control Clutch, Variable Speed, and Vario-Lock. Depth stop 310 mm (1 613 001 003); Machine cloth; Carrying case (2 605 438 651); Quick change chuck 13 mm (2 608 572 212); SDS plus quick-change chuck (2 608 572 213); Auxiliary handle (2 602 025 176); Grease tube (spare part number 1 615 430 010)

Article ID: 0611332101

### PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.