



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH ROTARY HAMMER WITH SDS PLUS GBH 4-32 DFR

SKU: 3165140600712

Rotary Hammer with SDS plus GBH 4-32 DFR

Categories: [BOSCH professional](#), [Drill & percussion hammers](#)

Product Features: Rated speed, from: 0 rpm
Rated speed, up to: 800 rpm
Rated speed: 0 - 800 rpm
Packaging dimensions (width): 360 mm
Packaging dimensions (length): 440 mm
Packaging dimensions (height): 155 mm
Packaging dimensions (width x length x height): 360 x 440 x 155 mm
Voltage, electrical: 230 V
Rated input power: 900 W
Impact energy (according to EPTA 05/2016): 4,2 J
Impact rate at rated speed, from: 0 bpm
Impact rate at rated speed, up to: 3.600 bpm
Impact rate at rated speed: 0 - 3,600 bpm
Weight: 4,7 kg
Tool dimensions (width): 377 mm
Tool dimensions (length): 493 mm
Tool dimensions (height): 133 mm
Tool holder: SDS plus
Drilling dia. concrete, hammer drill bits, from: 6 mm
Drilling dia. concrete, hammer drill bits, up to: 32 mm
Drilling dia. concrete, hammer drill bits: 6 - 32 mm
Rec. appl. range concrete, hammer drill bits, from: 14 mm
Rec. appl. range concrete, hammer drill bits, to: 25 mm
Opt. appl. range concrete, hammer drill bits: 14 - 25 mm



Max. drilling diameter masonry, core cutters:
90 mm

Max. drilling diameter in metal: 13 mm

Max. drilling diameter in wood: 32 mm

Product category subdivision: Rotary

Hammer with SDS plus

Positioning: Robustness combined with
durability and excellent performance in the
SDS plus category

User benefit incl. Reason to believe: 900 W
motor delivers 4.2 J of impact energy for very
fast chisel removal rates

User benefit incl. Reason to believe: Durable
due to robust metal gearbox housing design

User benefit incl. Reason to believe: Vibration
Control for effortless and continuous work in
time-intensive applications

Positioning (BE): The fastest multi-hammer in
the 4kg class

User benefit incl. Reason to believe (BE): Wide
range of applications in chiselling and drilling
work and when working with a core cutter

User benefit incl. Reason to believe (BE):

Drills up to 30% faster (25 mm diameter) than
other tools in its class

User benefit incl. Reason to believe (BE): Low
vibration levels of only 12 m/s² for less tiring
work due to Bosch Vibration Control

Areas of application: Drilling in concrete

Areas of application: Drilling in ferrous metals

Areas of application: Drilling in wood

Areas of application: Drilling in synthetic
material

Areas of application: Drilling in non-ferrous
metal

Areas of application: Drilling in stone

Areas of application: Dry drilling in stone

Areas of application: Chiselling in concrete

Areas of application: Chiselling in wood

Areas of application: Chiselling in stone

Areas of application: Screwdriving

Title: Rotary Hammer with SDS plus GBH 4-32
DFR Professional

Novelty: no

Scope of supply: Depth stop 310 mm (1 613
001 003)

Scope of supply: Machine cloth

Scope of supply: L-BOXX 136 (1 600 A01 2G0)



Scope of supply: Quick change chuck 13 mm
(2 608 572 212)

Scope of supply: SDS plus quick-change
chuck (2 608 572 213)

Scope of supply: Auxiliary handle (2 602 025
176)

Scope of supply: Grease tube (spare part
number 1 615 430 010)

Scope of supply: 1/1 L-BOXX inlay for tool (1
600 A00 2VH)

SOL Date: 01.08.2010

Scope of delivery:

1 ST Rotary Hammer with SDS plus GBH 4-32
DFR |

PRODUCT DESCRIPTION

Rotary Hammer with SDS plus GBH 4-32 DFR, The powerful GBH 4-32 DFR Professional with SDS plus delivers 4.2 J of impact energy with an 900 W motor for a very fast chisel removal rate. The rotary hammer is designed for durability, featuring a very robust metal gearbox housing. Its Vibration Control enables effortless and continuous work in time intensive applications. This rotary hammer is intended for drilling and chiselling in concrete, masonry, wood, and metal. It is compatible with various dust attachments. The GBH 4-32 DFR Professional also features a keyless and quick-change chuck, Reverse Mode, Rotation Control Clutch, Variable Speed, and Vario-Lock. Depth stop 310 mm (1 613 001 003); Machine cloth; L-BOXX 136 (1 600 A01 2G0); Quick change chuck 13 mm (2 608 572 212); SDS plus quick-change chuck (2 608 572 213); Auxiliary handle (2 602 025 176); Grease tube (spare part number 1 615 430 010); 1/1 L-BOXX inlay for tool (1 600 A00 2VH)

Article ID: 0611332104

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.