



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



**ROBERT BOSCH POWER TOOLS GMBH
SANDING SHEET F460
BFWP,G40,93MM. FOR OSCILLATING
MULTITOOLS**

SKU: 3165140959865

Sanding Sheet F460 BfWP,G40,93mm. For oscillating multitools

Categories: [Accessories for BOSCH professional](#), [Accessories for multifunctional tools](#), [Grinding and polishing](#)

Product Features: Sheet dimensions, width mm: 93
Sheet dimensions, length mm: 93
Sheet dimensions mm: 93x93
Grit: 40
Perforation: 6 holes
Benefit HL (short): Quality Finish
Performance Claim Text: Exceptional Finish
(Version) Key RTB: Durable F-/E backing paper for continuous work and professional finishes
Specific RTB1: High-quality semi-friable aluminium oxide and silicon carbide for precision material removal with perfect results
Specific RTB2: Electrostatically open-coated, and removes material with precision for optimal sanding behaviour
Specific RTB3: Fully synthetic resin binding on F-/E paper for wear resistance and long performance lifetime
Material: Paint on wood
Material: Hardwood
Material: Solid wood furniture board
Material: Parquet
Material: Multiplex board
Material: Particleboard
Material: Plastic coated boards
Product text, Accessories grey: Pack of 5



SOL Date: 01.01.2019

Novelty: no

Novelty until: 01.07.2019

Scope of delivery:

5 ST Sanding Sheet F460 BfWP,G40,93mm.

For oscillating multitools |

PRODUCT DESCRIPTION

The F460 Best for Wood and Paint produces an exceptional finish when keying and sanding wood as well as painted surfaces. Its F-/E backing paper is extremely durable, enabling continuous work and professional finishes. Furthermore, its high-quality semi-friable aluminium oxide and silicon carbide abrasive grit removes material with precision for perfect surface results. It is intended for flush sanding of edges and edge-strips and working on small surface pieces, as well as medium and fine sanding for surfaces, edges and rebates. It is also ideal for keying and the intermediate sanding of primers, fillers and varnishes. This sheet is coated with tough semi-friable aluminium oxide and silicon carbide for consistent surface quality. It is electrostatically open-coated and removes material with precision for optimal sanding behaviour. Furthermore, the grit is bonded using fully synthetic resin on the F-/E backing paper for wear resistance in heavy-duty applications, enabling a long performance lifetime.

Article ID: 2608621684

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.