



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

**ROBERT BOSCH POWER TOOLS GMBH  
STUB DRILL BITS, HSS-R, DIN 1897.  
FOR ROTARY DRILLS/DRIVERS**

**SKU:** 3165140099981

Stub drill bits, HSS-R, DIN 1897. For rotary drills/drivers

---

**Categories:** [Accessories for BOSCH professional](#), [Drilling](#)

**Product Features:** Diameter (D) mm: 4,00  
Working length (L1) mm: 22  
Total length (L2) mm: 55  
Benefit HL (short): Extra-Short Drill Bit for Drilling in Confined Spaces  
Performance Claim Text: For Confined Spaces (Version) Key RTB: The flute is an ideal working length for most types of tight work  
Specific RTB1: For effective drilling in areas with limited clearance, the self-centring split-point tip provides an easy start  
Specific RTB2: Manufactured to DIN 1897, drill bit Type N (flute angle) with a 118-degree tip, diameter tolerance h8  
Material: Steel sheets  
Material: Steel  
Material: Metal pipes and profiles  
Material: Non-ferrous metals  
Material: Aluminium  
Material: Plastics  
Material: Metal sandwich  
Product text, Accessories grey: Pack of 10  
SOL Date: 19.07.2002  
Novelty: no

Scope of delivery:  
1 ST Stub drill bits, HSS-R, DIN 1897. For rotary drills/drivers |









## PRODUCT DESCRIPTION

The HSS Stub Drill Bit is an extra-short drill bit for drilling in confined spaces, producing holes in sheet metals and pipes with a thickness of 2-6 mm. It offers a flute with an ideal working length for most types of tight work. An easy start without pre-punching is provided by the self-centring split-point tip, which prevents walking and enables effective drilling in areas with limited clearance. It is suitable for use on structural steel, alloyed metal, non-ferrous metal and plastics. This drill bit has a cylindrical shank system (shank equal to drill bit diameter) and is intended for use in drill stands and drill drivers. The HSS Stub Drill Bit is manufactured to DIN 1897. The drill bit is Type N (flute angle) with a 118-degree tip and a diameter tolerance of h8.

Article ID: 2608597231

## PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.