



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

ROD ELECTRODE FINCORD E 42 0 RR 12 3.2X450MM LOW ALLOY

SKU: 4028659103688

Rod electrode FINCORD E 42 0 RR 12
3.2x450mm low alloy



Categories: [Filler materials](#), [Rod electrodes](#)

Product Features: Weight: 5.7 kg

Length: 450 mm

EN ISO: E 42 0 RR 12

Ø: 3.2 mm

Sheath: Thick rutile

Scope of delivery:

5,70 KG Rod electrode FINCORD E 42 0 RR 12
3.2x450mm low alloy |

PRODUCT DESCRIPTION

Standard designation: EN ISO 2560-A: E 42 0 RR 12 AWS A-5.1: E6013 Low alloy

- Thick rutile coated Properties and area of application: Versatile, thick rutile rod electrode with excellent welding properties
- Easy to work with, so ideal for unpractised welders
- Easy ignition and re-ignition, all-position weldability
- Extremely low spatter arc, self-releasing slag in most cases
- Finely rippled, clean welds blend into base material with no undercut
- Increased current carrying capacity of larger dimensions from 3.2 x 450 mm
- Also used on mains lighting transformers
- FINCORD DB is recommended for X-ray-safe welds in conjunction with MAG-welded layers Base materials: S(P)235 - S(P)355
- GP240
- GP280 Approvals: TÜV / DB / ABS / BV / DNV / GL / LRS / CE Current type = - / ~ Welding position: PA, PB, PC, PD, PE, PF
- Prices per kilogram Further technical information:
- Contents: 118 pc.
- Alloy: Low alloy

PRODUCT DATASHEET LEGAL NOTE



Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.