



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

ROD ELECTRODE OVERCORD E 38 0 RC 11 2.5X350MM LOW ALLOY

SKU: 4028659105057

Rod electrode OVERCORD E 38 0 RC 11
2.5x350mm low alloy



Categories: [Filler materials](#), [Rod electrodes](#)

Product Features: Weight: 4.5 kg

Length: 350 mm

EN ISO: E 38 0 RC 11

Ø: 2.5 mm

Sheath: Rutile cellulose

Scope of delivery:

4,50 KG Rod electrode OVERCORD E 38 0 RC
11 2.5x350mm low alloy |

PRODUCT DESCRIPTION

Standard designation: EN ISO 2560-A: E38 0 RC 11 AWS A-5.1: E 6013 Low alloy

- Rutile cellulose coating Properties and area of application: For assembly, workshop and repair welds in all positions
- Excellent vertical down welding properties, reliable fusion penetration
- Assembly in any position without adjusting amperage
- Down welding produces smooth, slightly concave welds
- Easy to ignite and re-ignite
- Good bridging properties
- Suitable for primed and rusted parts, relatively insensitive to dirt in the welding area
- Powerful and stable electric arc means that OVERCORD can be used for galvanised steels
- Also used on mains lighting transformers
- If an additional arc is required, then OVERCORD Z should be selected Base materials: S(P)235 - S(P)355 - GP240
- GP280 Approvals: TÜV / DB / ABS / BV / DNV / GL / LRS / CE Current type = - / ~ Welding position: PA, PB, PC, PD, PE, PF, PG
- Prices per kilogram Further technical information:
- Contents: 275 pc.
- Alloy: Low alloy



PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.