



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



RUKO SET OF HAND TAPS DIN 352 3-PART M 20X PITCH 2.5 MM HSS BRIGHT, STRAIGHT, GROOVED ROUGHING/SECOND/BOTTOM. TAP TOL. ISO26H

SKU: 4007140024190

1,00 ST Set of hand taps DIN 352 3-part M 20x pitch 2.5 mm HSS bright, straight, grooved roughing/second/bottom. tap tol. ISO26H

Categories: [Sets of hand taps](#), [Threaded Tools](#)

Product Features: Standard: DIN 352
Nominal thread Ø: M20
Pitch: 2,5 mm
Overall length: 95 mm
Thread length: 40 mm
Square: 12 mm
Core hole Ø: 17,5 mm
Contents: 3-part
Brand: RUKO
Tolerance range: ISO2 (6H)
Type o

Scope of delivery:
1,00 ST Set of hand taps DIN 352 3-part M 20x pitch 2.5 mm HSS bright, straight, grooved roughing/second/bottom. tap tol. ISO26H |

PRODUCT DESCRIPTION

HSS

- Metric ISO thread
- DIN 13 Sheet 1
- Right-hand cutting
- Tolerance range ISO2 (6H)
- For unalloyed and low-alloy steels up to 800 N/mm² strength, malleable iron and non-ferrous metals 3-



part set comprising roughing tap, second tap, and finish tap Further technical information:

- Shank Ø: 16mm
- Cutting material: HSS

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.