Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



RUKO SUBLAND TWIST DRILL DIN 8376 TYPE N M10 HSS CYLINDER SHANK 180 DEG MEDIUM

SKU: 4007140109774

1,00 ST Subland twist drill DIN 8376 type N M10 HSS cylinder shank 180 deg medium

Categories: Drill Bits, Subland twist drills

Product Features: For nominal thread Ø: M10
Countersink Ø: 18 mm
Drilling Ø: 11 mm
Overall length: 191 mm
Length of step: 23 mm
Cutting direction: Right-hand cutting
Shank design: Straight shank
For thread: M10
Coa

Scope of delivery:
1,00 ST Subland twist drill DIN 8376 type N M10 HSS cylinder shank 180 deg medium |

PRODUCT DESCRIPTION

The bore and countersink are completed in one operation. Note: Set the cutting speed based on the large diameter and the feed rate based on the small diameter. For the rational production of through-hole bores and screw head joints with 90°. Further technical information:
- Feed in steel up to 800 N: 0,1mm/rev
- Point angle: 118°
- Type: N
- Type: Medium
- Countersink angle: 180°
- Length of chip groove: 130mm Note: The cutting speed depends on the large diameter, and the feed rate depends on the small diameter

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the

Copyright © 2023 Actik Tools All rights reserved

product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.

Copyright © 2023 Actik Tools

All rights reserved