



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

RUKO TWIST DRILL ULTIMATECUT DIN 338 TYPE N NOMINAL DM 1.5 MM HSS BRIGHT/BURNISHED CYLINDER SHANK 40 MM 5XDMRIGHT-HAND CUTTING

SKU: 4007140385772



10,00 ST Twist drill ULTIMATECUT DIN 338 type N nominal dm 1.5 mm HSS bright/burnished cylinder shank 40 mm 5xdmright-hand cutting

Categories: [Drill Bits](#), [Twist drills and accessories](#)

Product Features: Coating: Bright/burnished
Nominal Ø: 1.5 mm
Overall length: 40 mm
Length of spiral: 18 mm
Shank design: Straight shank
Point angle: 118 °
Mount Ø: 1.5 mm
Type: N
Standard: DIN 338
Cutting material

Scope of delivery:
10,00 ST Twist drill ULTIMATECUT DIN 338 type N nominal dm 1.5 mm HSS bright/burnished cylinder shank 40 mm 5xdmright-hand cutting |

PRODUCT DESCRIPTION

HSS

- DIN 338
- FLOWSTEP® tip
- Point angle 118°
- Right-hand cutting
- 3-surface shank
- Precise centring without punch-marking even on round surfaces, such as pipes



- Extremely fast spot drilling with low force requirement
- Drilling of large diameters without pre-drilling
- Smooth and silent drilling without tilting in the material
- 3-surface shank prevents spinning in the drill chuck
- Ideal for use in hand-held electric tools
- With straight shank Further technical information:
- Cutting direction: Right-hand cutting
- Feed in steel up to 800 N: 0,03mm/rev
- Nominal Ø tolerance: h8
- Overall length: 40mm

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.