



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



## SOUDAL SILICONE SEALANT SILIRUB BAU N TRANSPARENT 600 ML

**SKU:** 5411183122079

Silicone sealant Silirub Bau N transparent 600

**Categories:** Chemical-technical products, Silicones

**Product Features:** Colour: Transparent

Contents: 600 ml Container: Bag

Networking system: Neutral cross-linking

Thermal resistance: -60 to +150 °C

Brand: SOUDAL

Scope of delivery: 12,00 ST Silicone sealant Silirub Bau N transparent 600 ml |

## PRODUCT DESCRIPTION

A high-quality, neutral cross-linking, permanently elastic, silicone-based, 1-component joint sealant

- For construction and structural joints, durable, vapour diffusion permeable, external sealing of joints between masonry/door and window frames
- Glass/frame sealing in conjunction with coated wood, anodised aluminium and rigid PVC
- Seals in container construction, connection profiles, flashing for plumbing and roofing works on roofs, terraces and entrances (e.g. fireplace connections, openings for ventilation ducts, aerials and skylights)
- Tested to ISO 11600-F+G-25LM
- Very good colourfast properties, weather and UV-resistant
- Permanently elastic after curing
- Corrosion-proof
- Coating compatible to DIN 52452-A1 (cannot be painted over) Further technical information:
- Construction material class: To DIN 4102: B2
- Curing time: Approx. 2 mm/24 h
- Processing temperature: +5 to +35°C

## PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the





product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.

Copyright © 2023 Actik Tools All rights reserved