



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

## STABILA ROTATING LASER SET LAR 160 G 600 M 4-PART +/- 5 DEG

SKU: 4005069192402

1,00 ST Rotating laser set LAR 160 G 600 m 4-part +/- 5 deg



Categories: [Laser technology](#), [Surveying technology](#)

**Product Features:** Work area: 600 m  
Levelling accuracy: +/- 0.1 mm/m  
Self-levelling range: +/- 5 °  
Laser class: 2  
Weight: 1.81 kg  
Operating temperature: -10 to +50 °C  
Type: 4-part  
Brand: STABILA

Scope of delivery:  
1,00 ST Rotating laser set LAR 160 G 600 m 4-part +/- 5 deg |

## PRODUCT DESCRIPTION

Fully automatic, motorised rotating laser - high levelling accuracy +/- 0.1 mm/m, rapid self-levelling within 20 seconds

- STABILA GREENBEAM technology for better visibility of the rotating laser beam - green laser beams are 4 times more visible to the human eye than red beams
- Four laser functions for versatile application - horizontal and vertical rotation, plumb function and right angle (90°) in vertical mode
- Protection class IP 65 - dust-protected and waterproof
- Shock-absorbing STABILA soft grip shell protects against impacts - the laser optics is additionally protected by the stable housing head
- Easy operation using three control buttons - on/off, tilt mode, manual mode
- Battery drawer - easy replacement, even directly on the tripod
- Large working range with set receiver REC 160 RG - up to 600 m diameter
- Two 5/8" threads integrated into the housing
- Target plate with magnetic mounting and cross-hair For a range of tasks in dry construction - for layout work, setting partition walls and suspending ceilings. Quickly and easily transfer heights for electric installation work - horizontal and vertical alignment of sockets, switches and cable ducts. For installation



work in industrial construction - measuring levels and determining alignments for cable and pipe runs. In industrial assembly - measuring and aligning shelving systems in logistics areas. Further technical information:

- Protection class: IP 65

- Operating time: 20h Scope of supply: Rotating laser LAR 160 G, receiver REC 160 RG, target plate, carry case, 2 x D 1.5 V batteries, 2 x AA 1.5 V batteries Note on the disposal of batteries and rechargeable batteries As we sell batteries and rechargeable batteries and devices that contain batteries and rechargeable batteries, under the German Battery Act (BattG we are obliged to draw your attention to the following: The symbol of the waste bin with the X through it on batteries and rechargeable batteries means that they must not be disposed on in household waste after consumption. If batteries or rechargeable batteries contain mercury, cadmium or lead, you will find the chemical symbol (Hg, Cd or Pb) under the symbol of the waste bin with the X through it. Every user of batteries or rechargeable batteries is legally obliged to return old batteries and rechargeable batteries. They can be returned, free of charge, to the retailer or another collection point near you. You can obtain the addresses of suitable collection points near you from your local government authority. In the case of batteries that contain more than 0.0005 percent by mass mercury, more than 0.002 percent by mass cadmium or more than 0.004 percent by mass lead, the chemical symbols of the respective harmful substance used are indicated under the waste bin symbol. The chemical symbols have the following meaning: Pb: Battery contains lead Cd: Battery contains cadmium Hg: Battery contains mercury

#### PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.