



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



UHU ADHESIVE AND SEALING AGENT POLY MAX 10 SEC IMMEDIATE POWER WHITE 425 G

SKU: 4026700472301

Adhesive and sealing agent POLY MAX 10 SEC
IMMEDIATE POWER white 425 g

Categories: [Assembly adhesives and accessories](#), [Chemical-technical products](#)

Product Features: Colour: White

Contents: 425 g

Container: Cartridge

Brand: UHU

Scope of delivery:

12,00 ST Adhesive and sealing agent POLY
MAX 10 SEC IMMEDIATE POWER white 425 g

|

PRODUCT DESCRIPTION

Universal, high-quality assembly adhesive and sealant based on UHU polymer technology

- With high initial strength and very quick build-up of thickness
 - Bonds, mounts and seals almost all (construction) materials onto almost all surfaces (smooth, porous and non-porous surfaces)
 - Particularly suitable for heavy-duty materials
 - For indoors and outdoors
 - Water resistant & weather-resistant
 - Free from solvents and acids, odourless
 - Can be painted over after curing (test beforehand)
 - Temperature-resistant from -40 °C to +100 °C
 - Bonds, among other things, wood, many plastics and metals, natural stone/stone, concrete, glass, gypsum, chipboards, cork, plaster, ceramic tiles
 - Bonds, among other things, mirrors, skirting boards, slats, slatted structures, window sills, thresholds, gable and cavity panels, stucco work, panels, decorative beading, strips, fascias
 - Seals, among other things, joints, seals, slots, connection joints on frames, fascias, skylights
- Further technical information:
- Curing time: Approx. 3 mm/24 h
 - Chemical basis: Silane-modified polymer



- Processing temperature: +5 °C to +40°C
- Wet life of glue: Approx. 30min.
- Thermal resistance: -40 °C to +100 °C

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.