



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



WEICON HYDRAULIC/PNEUMATIC SEAL WEICONLOCK® AN 305-42 MEDIUM STRENGTH, MEDIUM VISCOSITY BROWN 50 ML

SKU: 4024596020767

Hydraulic/pneumatic seal WEICONLOCK® AN 305-42 medium strength, medium viscosity brown 50 ml

Categories: Chemical-technical products, Surface, pipe and screw thread seals

Product Features: Contents: 50 ml Brand: WEICON safety instructions

Scope of delivery: 1,00 ST Hydraulic/pneumatic seal WEICONLOCK® AN 305-42 medium strength, medium viscosity brown 50 ml |

PRODUCT DESCRIPTION

Universal application

- With DVGW approval
- Medium-strength
- Normal dismantling capability
- Gap bridging: Max. 0.15 mm
- Thread size: Up to M 20 R ¾"
- Breakaway torque: 12-15 Nm (determined for screws M 10, quality 8.8, nut height 0.8.d)
- Handling strength between 10-20 min, (at room temperature)
- Final strength after 2-4 hours (at room temperature)
- Temperature-resistant from -60 °C to +150 °C Further technical information:
- Gap filling capacity: Max. 0.15mm
- Colour: Brown
- Viscosity: Medium-viscosityBreakaway torque: 12-15Nm
- Hand-tight: 10-20min
- Thermal resistance: -60 to +150 °C
- Thread: Max. M20 R 3/4





- Strength: Medium-strength

- Container: Pen - Approval: DVGW

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.

Copyright © 2023 Actik Tools All rights reserved